

# Klemsan®

## UTOR

Isolated USB - RS485 / RS232 / TTL Converter  
Convertor Aislado USB - RS485 / RS232 / TTL

type / tipo	product description/ descripción del producto	isolation / aislamiento	orden no / No. de orden
UTOR-4i	Isolated USB - RS485 converter / Convertor aislado USB – RS485	2500Vrms	601 430
UTOR-2i	Isolated USB - RS232 converter / Convertor aislado USB – RS232	2500Vrms	601 431
UTOR-T5i	Isolated USB - TTL (5V) converter / Convertor aislado USB – TTL (5V)	2500Vrms	601 432
UTOR-T3i	Isolated USB - TTL (3.3V) converter / Convertor aislado USB – TTL (3.3V)	2500Vrms	601 433

### technical specifications

USB	USB 1.1 and USB 2.0
Baud Rate	300 .. 115200 bps
Isolation	2500Vrms
Humidity	Max. %95, non-condensing
Operating Temperature	-20°C .. 60°C
Storage Temperature	-20°C .. 70°C

### especificaciones técnicas

USB	USB 1.1 y USB 2.0
Tasa de transferencia	300 .. 115200 bps
Aislamiento	2500Vrms
Humedad	Máx. 95%, sin condensación
Temperatura de operación	-20°C .. 60°C
Temperatura de almacenamiento	-20°C .. 70°C