

ELECTRONICS PRODUCTS > ENERGY MANAGEMENT PRODUCTS > ENERGY METERS

145-0M-01

Stock Keeping Unit (SKU): 606362*1Ø Energy Meter*

Commercial Information

Product Sales Code	606362
Package Unit	1 pcs.
Customs Tariff Number	903032009011
Weight Per Unit Including Packaging	0.08 kg.

Technical Information

General

Connection Type	1P2W
Real Time Clock	-
Current Connection Type	Direkt Baglantili (45A ya kadar)
Alarm	+

Energy Measurement

Number Of Tariffs	1
Number Of Sub Tariffs	-
Number Of Reactive Measurement Zones	2
Energy Measurement Type	Import & Export kWh-kVARh
Partial Counter	
Balance Energy	

Current Measurement Input

Measuring Range	0,25 .. 45A
-----------------	--------------------

Voltage Measurement Input

Measuring Range L N	100-300V AC
---------------------	--------------------

Measuring Range L L	-
---------------------	---

Power Quality Measurements

Harmonic Measurement Current And Voltage	-
--	---

Thdi	+
------	---

Thdv	+
------	---

Power Supply

Voltage	100-300V AC
---------	--------------------

Frequency	45-65Hz
-----------	----------------

Consumption	<3VA AC
-------------	-------------------

Mechanical Properties

Weight G	80
----------	-----------

Protection Class	IP20
------------------	-------------

Mounting Type	Rail Mount
---------------	-------------------

Environmental Conditions

Operating Temperature	-25°C +50°C
-----------------------	--------------------

Storage Temperature	-25°C +70°C
---------------------	--------------------

Relative Humidity Non Condensing	Max. 80% (no condensation)
----------------------------------	-----------------------------------

Communication

Protocol	Modbus RTU
----------	-------------------

Baud Rate	1200-115200
-----------	--------------------

Parity	Odd, Even, None
--------	------------------------

Stop Bit	1
----------	----------

Slave Id	1-247
----------	--------------

Isolation	2750V RMS
-----------	------------------

Digital Output

Frequency	5-30 VDC
-----------	-----------------

Number Of Inputs	1 (sabit)
Switched Voltage Range	Transistor
Isolation	3750 Vrms

Digital Input

Number Of Inputs	
Input Type	
Isolation	

Other Measurements

Operating Time Counter	
Open Time Counter	
Power Failure Counter	

Basic Electrical Measurements

Current	+
Voltage	+
Frequency	+
Active Power	+
Reactive Power	+
Apparent Power	+

Cable Cross Sections Power Supply Voltage Relay

multi-core	
Single Core	

Cable Cross Sections Current

multi-core	
Single Core	

Cable Cross Sections Digital Inputoutput Rs485 Analog Output

multi-core	
Single Core	

Measurement Class

En 50470	
62053 21	Class 1

Measurement

Max Min Data	
Demand	

Led Impulse

Kwh	+
Kvarh	