

ELECTRONICS PRODUCTS > COMMUNICATION INTERFACES > GATEWAY



2G & 3G GPRS Gateway

Stock Keeping Unit (SKU): 601445

2G & 3G GPRS Gateway

Commercial Information

| | |
|--------------------|---------------|
| Product Sales Code | 601445 |
| Package Unit | 1 pcs. |

Technical Information

CONNECTION DATA

| | |
|-----------------|-----------------------|
| Connection Type | Screw terminal |
|-----------------|-----------------------|

General

| | |
|-------------------------------|--|
| Case Width Mm | 17,5 |
| Configuration | |
| Dhcp Automatic Ip Acquisition | |
| Ping Blocking | |
| Led Indicators | + |
| Reset Function | + |
| Esd Protection | + |
| Supported Drivers | Microsoft .NET Framework 3.5 üzeri windows işletim sistemleri |
| Supported Protocols | |
| Isolation | 1.5kV RMS |

Power Supply

| | |
|---------|-----------------|
| Voltage | 11-30VDC |
|---------|-----------------|

| | |
|-------------|------------------|
| Frequency | 45-65Hz |
| Consumption | 11-30V DC |

Mechanical Properties

| | |
|--------------------|-------------------|
| Weight G | |
| Protection Class | IP20 |
| Mounting Type | Rail Mount |
| Packaging Quantity | 1 |

Environmental Conditions

| | |
|----------------------------------|----------------------------------|
| Operating Temperature | |
| Storage Temperature | -30°C..+80°C |
| Relative Humidity Non Condensing | Max.95% (no condensation) |

Serial Interface

| | |
|----------------------------|--------------------------|
| Number Of Ports | 1 |
| Serial Connection Standard | RS485 |
| Server Mode | 64 |
| Receiver Mode | 64 |
| Baud Rate | 300 to 115200 bps |
| Data Bits | 8 |
| Stop Bits | 1-2 |
| Parity | None, even, odd |

Gprs Multi Slot Class

| | |
|----------|-------------------------------|
| Downlink | Class 12 Max. 85.6kbps |
| Uplink | Class 12 Max. 85.6kbps |

Edge Multi Slot Class

| | |
|----------|--------------------------------|
| Downlink | Class 12 Max. 236.8kbps |
| Uplink | Class 12 Max. 236.8kbps |

Communication

| | |
|---------------------|--|
| Auxiliary Protocols | MODBUS TCP; MODBUS RTU via TCP; MODBUS ACII via TCP |
|---------------------|--|

| | |
|----------------|--|
| Operation Type | Serial Master; Transparent |
| Logging | 7-days record (1 ... 60 min) Totally 100,800 records (1 min resolution) |
