

ELECTRONICS PRODUCTS > COMMUNICATION INTERFACES > GATEWAY



## 2G GPRS Gateway

Stock Keeping Unit (SKU): 601440

2G GPRS Gateway

### Commercial Information

Product Sales Code	<b>601440</b>
Package Unit	<b>1 pcs.</b>

### Technical Information

#### CONNECTION DATA

Connection Type	<b>Screw terminal</b>
-----------------	-----------------------

#### General

Case Width Mm	<b>17,5</b>
Configuration	<b>Configuration through USB Micro USB connection interface</b>
Led Indicators	<b>+</b>
Reset Function	<b>+</b>
Esd Protection	<b>+</b>
Supported Drivers	<b>Microsoft .NET Framework 3.5 üzeri windows işletim sistemleri</b>
Supported Protocols	<b>MODBUS TCP; MODBUS RTU over TCP; MODBUS ACII over TCP</b>
Isolation	<b>1.5kV RMS</b>

#### Power Supply

Voltage	<b>11-30VDC</b>
Frequency	<b>45-65Hz</b>
Consumption	<b>1.2W DC</b>

## Mechanical Properties

Weight G	
Protection Class	<b>IP20</b>
Mounting Type	
Packaging Quantity	<b>1</b>

## Environmental Conditions

Operating Temperature	
Storage Temperature	
Relative Humidity Non Condensing	<b>%95 non-condensing</b>

## Serial Interface

Number Of Ports	<b>1</b>
Serial Connection Standard	<b>RS485</b>
Server Mode	<b>64</b>
Receiver Mode	<b>(-)</b>
Baud Rate	<b>300 to 115200 bps</b>
Data Bits	<b>8</b>
Stop Bits	<b>1 or 2</b>
Parity	<b>---, Double, Single</b>

## Gprs Interface

Simusim	<b>3V/1.8V</b>
Quad Band	<b>850/900/1800/1900MHz</b>
Downlink	<b>Class 12 85.6kbps</b>
Uplink	<b>Class 12 85.6kbps</b>
Gprs Mobile Station	<b>Class B</b>
Compliant To Gsm Phase 22	<b>Phase 2/2+ Class 4 (2W @850/900MHz) Class 1 (1W @1800/1900MHz)</b>