

ELECTRONICS PRODUCTS > ENERGY MANAGEMENT PRODUCTS > ENERGY METERS



## 5100-1Q-V2CT

Stock Keeping Unit (SKU): 606817

3Ø MID Energy Meter

### Commercial Information

Product Sales Code	<b>606817</b>
Package Unit	<b>1 pcs.</b>
Customs Tariff Number	<b>903032009011</b>
Weight Per Unit Including Packaging	<b>0.34 kg.</b>

### Technical Information

#### General

Connection Type	<b>3P4W &amp; 3P3W</b>
Real Time Clock	
Current Connection Type	<b>CT Baglantili</b>
Alarm	

#### Energy Measurement

Number Of Tariffs	<b>2</b>
Number Of Sub Tariffs	
Number Of Reactive Measurement Zones	<b>4</b>
Energy Measurement Type	<b>Import &amp; Export kWh-kVArh</b>
Partial Counter	
Balance Energy	<b>+</b>

## Current Measurement Input

Measuring Range	<b>0,05 .. 6A</b>
-----------------	-------------------

## Voltage Measurement Input

Measuring Range L N	<b>100-300V AC</b>
---------------------	--------------------

Measuring Range L L	<b>173-520</b>
---------------------	----------------

## Power Quality Measurements

Harmonic Measurement Current And Voltage	
------------------------------------------	--

Thdi	<b>+</b>
------	----------

Thdv	<b>+</b>
------	----------

## Power Supply

Voltage	<b>100-300V AC</b>
---------	--------------------

Frequency	<b>45-65Hz</b>
-----------	----------------

Consumption	<b>&lt;3VA AC</b>
-------------	-------------------

## Mechanical Properties

Weight G	<b>340</b>
----------	------------

Protection Class	<b>IP20</b>
------------------	-------------

Mounting Type	<b>Rail Mount</b>
---------------	-------------------

## Environmental Conditions

Operating Temperature	<b>-25°C +50°C</b>
-----------------------	--------------------

Storage Temperature	<b>-25°C +70°C</b>
---------------------	--------------------

Relative Humidity Non Condensing	<b>Max. 80% (no condensation)</b>
----------------------------------	-----------------------------------

## Communication

Protocol	<b>Modbus RTU</b>
----------	-------------------

Baud Rate	<b>1200-57600</b>
-----------	-------------------

Parity	<b>Odd, Even, None</b>
--------	------------------------

Stop Bit	<b>1</b>
----------	----------

Slave Id	<b>1-247</b>
----------	--------------

Isolation	<b>3750 Vrms</b>
-----------	------------------

## Digital Output

Frequency	<b>5-30 VDC</b>
Number Of Inputs	<b>2 (1 sabit, 1 ayarlanabilir)</b>
Switched Voltage Range	<b>Transistor</b>
Isolation	<b>3750 Vrms</b>

## Digital Input

Number Of Inputs	<b>2</b>
Input Type	<b>Dry Contact</b>
Isolation	<b>3750 Vrms</b>

## Other Measurements

Operating Time Counter	
Open Time Counter	
Power Failure Counter	

## Basic Electrical Measurements

Current	<b>+</b>
Voltage	<b>+</b>
Frequency	<b>+</b>
Active Power	<b>+</b>
Reactive Power	<b>+</b>
Apparent Power	<b>+</b>

## Cable Cross Sections Power Supply Voltage Relay

multi-core	
Single Core	

## Cable Cross Sections Current

multi-core	
Single Core	

## Cable Cross Sections Digital Inputoutput Rs485 Analog Output

multi-core	
------------	--

Single Core

### Measurement Class

En 50470

**Class B**

62053 21

### Measurement

Max Min Data

Demand

**+**

### Led Impulse

Kwh

**+**

Kvarh

**+**