

ELECTRONICS PRODUCTS > ENERGY MANAGEMENT PRODUCTS > ENERGY METERS



## 580-1M-V3

**Stock Keeping Unit (SKU):** 606373

*1Ø Energy Meter*

### Commercial Information

Product Sales Code	<b>606373</b>
Package Unit	<b>1 pcs.</b>
Customs Tariff Number	<b>903032009011</b>
Weight Per Unit Including Packaging	<b>0.12 kg.</b>

### Technical Information

General	
Connection Type	<b>1P2W</b>
Real Time Clock	<b>+</b>
Current Connection Type	<b>Direkt Bağlantili (45A ya kadar)</b>
Alarm	<b>+</b>
Energy Measurement	
Number Of Tariffs	<b>2</b>
Number Of Sub Tariffs	<b>4</b>
Number Of Reactive Measurement Zones	<b>2</b>
Energy Measurement Type	<b>Import &amp; Export kWh-kVArh</b>
Partial Counter	
Balance Energy	

## Current Measurement Input

Measuring Range	<b>0,15 .. 80A</b>
-----------------	--------------------

## Voltage Measurement Input

Measuring Range L N	<b>100-300V AC</b>
---------------------	--------------------

Measuring Range L L	-
---------------------	---

## Power Quality Measurements

Harmonic Measurement Current And Voltage	<b>31</b>
--	-----------

Thdi	<b>+</b>
------	----------

Thdv	<b>+</b>
------	----------

## Power Supply

Voltage	<b>100-300V AC</b>
---------	--------------------

Frequency	<b>45-65Hz</b>
-----------	----------------

Consumption	<b>&lt;3VA AC</b>
-------------	-------------------

## Mechanical Properties

Weight G	<b>120</b>
----------	------------

Protection Class	<b>IP20</b>
------------------	-------------

Mounting Type	<b>Rail Mount</b>
---------------	-------------------

## Environmental Conditions

Operating Temperature	<b>-25°C +50°C</b>
-----------------------	--------------------

Storage Temperature	<b>-25°C +70°C</b>
---------------------	--------------------

Relative Humidity Non Condensing	<b>Max. 80% (no condensation)</b>
----------------------------------	-----------------------------------

## Communication

Protocol	<b>Modbus RTU</b>
----------	-------------------

Baud Rate	<b>1200-115200</b>
-----------	--------------------

Parity	<b>Odd, Even, None</b>
--------	------------------------

Stop Bit	<b>1</b>
----------	----------

Slave Id	<b>1-247</b>
----------	--------------

Isolation	<b>2750V RMS</b>
-----------	------------------

## Digital Output

Frequency	<b>5-30 VDC</b>
-----------	-----------------

Number Of Inputs	<b>2 (Ayarlanabilir)</b>
------------------	--------------------------

Switched Voltage Range	<b>Transistor</b>
------------------------	-------------------

Isolation	<b>3750 Vrms</b>
-----------	------------------

## Digital Input

Number Of Inputs	
------------------	--

Input Type	
------------	--

Isolation	
-----------	--

## Other Measurements

Operating Time Counter	
------------------------	--

Open Time Counter	
-------------------	--

Power Failure Counter	
-----------------------	--

## Basic Electrical Measurements

Current	<b>+</b>
---------	----------

Voltage	<b>+</b>
---------	----------

Frequency	<b>+</b>
-----------	----------

Active Power	<b>+</b>
--------------	----------

Reactive Power	<b>+</b>
----------------	----------

Apparent Power	<b>+</b>
----------------	----------

## Cable Cross Sections Power Supply Voltage Relay

multi-core	
------------	--

Single Core	
-------------	--

## Cable Cross Sections Current

multi-core	
------------	--

Single Core	
-------------	--

## Cable Cross Sections Digital Inputoutput Rs485 Analog Output

multi-core	
------------	--

Single Core

### Measurement Class

En 50470

62053 21

**Class 1**

### Measurement

Max Min Data

Demand

### Led Impulse

Kwh

+

Kvarh

+