

ELECTRONICS PRODUCTS > ENERGY MANAGEMENT PRODUCTS > ALARM ANNUNCIATORS



## ALRC-6(110VAC/DC)

**Stock Keeping Unit (SKU):** 604612

*Alarm Control Relay*

### Commercial Information

Product Sales Code	<b>604612</b>
Package Unit	<b>1 pcs.</b>
Customs Tariff Number	<b>853180709000</b>

### Technical Information

General	
Connection Type	<b>Screw terminal</b>
Time Interval	----
Integrated Buttons	<b>3 (Horn, Delete, Test)</b>
Siren	---
Real Time Data Recording	---
Battery Life	---
Protection Class	<b>IP50 (front)IP20 (back)</b>
Weight G	<b>274</b>
Packaging Quantity	<b>1</b>
Diagrams	---
DIMENSIONS	---
Power Supply	
Frequency	<b>45-65Hz</b>
Consumption	<b>AC/DC 110V ± %30</b>

## Environmental Conditions

Operating Temperature	<b>-20°C +60°C</b>
Storage Temperature	<b>-40°C +75°C</b>
Relative Humidity Non Condensing	<b>Max. 95%</b>

## Communication

Protocol	----
Baud Rate	----
Parity	
Stop Bit	
Slave Id	
Isolation	----

## Input Signal

Voltage	<b>AC / DC 110V</b>
Frequency	<b>45-65Hz</b>
Quantity	<b>6</b>
Response Time	<b>25±10ms</b>

## Output Connections

Output Type	<b>Relay</b>
Number of Connections	<b>8</b>
Type	<b>1 NO (SPST)</b>
Max Values Ac	<b>5A/277V;1385VA</b>
Max Values Dc	<b>5A/30VDC;150W</b>
Mechanical Operating Life	<b>=10<sup>8</sup> operation</b>
Electrical Operating Life No Side	<b>1x10<sup>5</sup> (5A@250VAC)</b>

## Window

Quantity	<b>6</b>
Color	<b>Red</b>
Size Mm	<b>30.5 x 21.6</b>
Illumination	<b>With 4 pcs. red leds</b>

Fast Flashing	<b>90 Flash / Min.</b>
Slow Flashing	---
Marking	<b>Laser printed onto standart tracing paper, using templates provided bu Klemsan Inc.</b>

## DIMENSIONS

Frontoverall Dimensions Height Mm	<b>96</b>
Frontoverall Dimensions Width Mm	<b>96</b>
Panel Cutout Dimensions Height Mm	<b>89.6</b>
Panel Cutout Dimensions Width Mm	<b>89.6</b>
Panel Cutout Dimensions Depth Mm	<b>66</b>