



ELECTRONICS PRODUCTS > ENERGY MANAGEMENT PRODUCTS > ALARM ANNUNCIATORS

ANC-24 (24V AC/DC, 85-300V AC/DC p.s.)

Stock Keeping Unit (SKU): 604660

Alarm Annunciator

Commercial Information

| | |
|-------------------------------------|---------------------|
| Product Sales Code | 604660 |
| Package Unit | 1 pcs. |
| Customs Tariff Number | 853180709000 |
| Weight Per Unit Including Packaging | 540g kg. |

Technical Information

| General | |
|--------------------------|--|
| Connection Type | Screw terminal |
| Time Interval | 0,2,5,10,15,20,25,30 adjustable |
| Integrated Buttons | 4 (Horn, Ack, Delete, Test) |
| Siren | + |
| Real Time Data Recording | 6080 logs |
| Battery Life | > 5 years |
| Protection Class | IP50 (front)IP20 (back) |
| Weight G | 540 |
| Packaging Quantity | 1 |
| Diagrams | --- |
| DIMENSIONS | --- |

Power Supply

| | |
|-----------|--------------------------------|
| Voltage | <10VA DC / <5W AC |
| Frequency | 45-65Hz |

Environmental Conditions

| | |
|----------------------------------|----------------------------------|
| Operating Temperature | -20°C +60°C |
| Storage Temperature | -40°C +75°C |
| Relative Humidity Non Condensing | Max.95% (no condensation) |

Communication

| | |
|-----------|-------------------|
| Protocol | Modbus RTU |
| Baud Rate | 1200-57600 |
| Parity | |
| Stop Bit | |
| Slave Id | |
| Isolation | 2500Vrms |

Input Signal

| | |
|---------------|--------------------|
| Voltage | 24V AC / DC |
| Frequency | 45-65Hz |
| Quantity | 24 |
| Response Time | 25±10ms |

Output Connections

| | |
|-----------------------------------|------------------------------------|
| Output Type | Relay |
| Number of Connections | 2 |
| Type | 1 NO (SPST) |
| Max Values Ac | 5A/277V;1385VA |
| Max Values Dc | 5A/30VDC;150W |
| Mechanical Operating Life | =10⁸ operation |
| Electrical Operating Life No Side | 1x10⁸(5A@250VAC) |

Window

| | |
|----------|-----------|
| Quantity | 24 |
|----------|-----------|

| | |
|---------------|--|
| Color | Red / Green selectable |
| Size Mm | 24,4x11,9 |
| Illumination | With 2 pcs. red leds or 2 pcs. green led |
| Fast Flashing | 180 Flash / Min |
| Slow Flashing | 60 Flash / Min. |
| Marking | Laser printed onto standart tracing paper, using templates provided bu Klemsan Inc. |

DIMENSIONS

| | |
|-----------------------------------|------------|
| Frontoverall Dimensions Height Mm | 144 |
| Frontoverall Dimensions Width Mm | 137 |
| Panel Cutout Dimensions Height Mm | 137 |
| Panel Cutout Dimensions Width Mm | 137 |
| Panel Cutout Dimensions Depth Mm | |