



ELECTRONICS PRODUCTS > ENERGY MANAGEMENT PRODUCTS > ALARM ANNUNCIATORS

ANC32 (48V AC/DC)

Stock Keeping Unit (SKU): 604671

Alarm Annunciator, 32 Channels, 48V AC/DC Signal Input, 85-300 V AC/DC Supply Input

Commercial Information

Product Sales Code	604671
Package Unit	1 pcs.
Customs Tariff Number	853180709000
Weight Per Unit Including Packaging	540g kg.

Technical Information

GENERAL	
Connection Type	Screw terminal
Time Range	0,2,5,10,15,20,25,30 adjustable
Integrated Buttons	4 (Horn, Ack, Delete, Test)
Siren	+
Real-Time Data Logging	6080 logs
Battery Life	> 5 years
Protection Class	IP20
Weight (g)	540
Pack Quantity	1
Diagrams	---
Dimensions	---
POWER SUPPLY	
Voltage	<5W DC / <10VA AC

Frequency	45-65Hz
-----------	---------

ENVIRONMENTAL CONDITIONS

Operating Temperature	-20°C +60°C
Storage Temperature	-40°C +75°C
Relative Humidity (Non-condensing)	Max.95% (no condensation)

COMMUNICATION

Protocol	Modbus RTU
Baud Rate	1200-57600
Parity	
Stop Bit	
Slave ID	
Insulation	2500Vrms

INPUT SIGNAL

Voltage	48V AC / DC
Frequency	45-65Hz
Piece	32
Response Time	25±10ms

OUTPUT CONNECTIONS

OUTPUT TYPE	Relay
Number of Connections	2
Type	1 NO (SPST)
Max. AC Ratings	5A/277V;1385VA
Max. DC Ratings	5A/30VDC;150W
Mechanical Service Life	=10^8 operation
Electrical Service Life (NO Contact)	1x10^5(5A@250VAC)

WINDOW

Piece	32
Color	Red / Green selectable

Size (mm)	15,3 x 11,9
Illumination	With 2 pcs. red leds or 2 pcs. green led
Fast Flashing	180 Flash / Min
Slow Flashing	60 Flash / Min.
Marking	Laser printed onto standart tracing paper, using templates provided bu Klemsan Inc.

Dimensions	
Front Face Overall Dimensions - Height (mm)	144
Front Face Overall Dimensions - Width (mm)	144
Panel Cut-Out Dimensions - Height (mm)	
Panel Cut-Out Dimensions - Width (mm)	
Panel Cut-Out Dimensions - Depth (mm)	