

ELECTRONICS PRODUCTS > ENERGY MANAGEMENT PRODUCTS > ALARM ANNUNCIATORS

ANC32 (48V AC/DC)

Stock Keeping Unit (SKU): 604671

Alarm Annunciator, 32 Channels, 48V AC/DC Signal Input, 85-300 V AC/DC Supply Input

Commercial Information

Product Sales Code	**604671**
Package Unit	**1 pcs.**
Customs Tariff Number	**853180709000**
Weight Per Unit Including Packaging	**540g kg.**

Technical Information

GENERAL	
Connection Type	**Screw terminal**
Time Range	**0,2,5,10,15,20,25,30 adjustable**
Integrated Buttons	**4 (Horn, Ack, Delete, Test)**
Siren	**+**
Real-Time Data Logging	**6080 logs**
Battery Life	**> 5 years**
Protection Class	**IP20**
Weight (g)	**540**
Pack Quantity	**1**
Diagrams	**---**
Dimensions	**---**

POWER SUPPLY	
Voltage	**<5W DC / <10VA AC**

Frequency	**45-65Hz**

ENVIRONMENTAL CONDITIONS

Operating Temperature	**-20°C +60°C**
Storage Temperature	**-40°C +75°C**
Relative Humidity (Non-condensing)	**Max.95% (no condensation)**

COMMUNICATION

Protocol	**Modbus RTU**
Baud Rate	**1200-57600**
Parity	
Stop Bit	
Slave ID	
Insulation	**2500Vrms**

INPUT SIGNAL

Voltage	**48V AC / DC**
Frequency	**45-65Hz**
Piece	**32**
Response Time	**25±10ms**

OUTPUT CONNECTIONS

OUTPUT TYPE	**Relay**
Number of Connections	**2**
Type	**1 NO (SPST)**
Max. AC Ratings	**5A/277V;1385VA**
Max. DC Ratings	**5A/30VDC;150W**
Mechanical Service Life	**=10^8 operation**
Electrical Service Life (NO Contact)	**1x10^5(5A@250VAC)**

WINDOW

Piece	**32**
Color	**Red / Green selectable**

Size (mm)	**15,3 x 11,9**
Illumination	**With 2 pcs. red leds or 2 pcs. green led**
Fast Flashing	**180 Flash / Min**
Slow Flashing	**60 Flash / Min.**
Marking	**Laser printed onto standart tracing paper, using templates provided bu Klemsan Inc.**

Dimensions	
Front Face Overall Dimensions - Height (mm)	**144**
Front Face Overall Dimensions - Width (mm)	**144**
Panel Cut-Out Dimensions - Height (mm)	
Panel Cut-Out Dimensions - Width (mm)	
Panel Cut-Out Dimensions - Depth (mm)	

Certificates

CE

UKRAYNA

TSE