

ELECTRONICS PRODUCTS > ENERGY MANAGEMENT PRODUCTS > ALARM ANNUNCIATORS



ANC-8(110VAC/DC)

Stock Keeping Unit (SKU): 604622

Digital Alarm Annunciator

Commercial Information

| | |
|-------------------------------------|---------------------|
| Product Sales Code | 604622 |
| Package Unit | 1 pcs. |
| Customs Tariff Number | 853180709000 |
| Weight Per Unit Including Packaging | 280g kg. |

Technical Information

| General | |
|--------------------------|----------------------------------------|
| Connection Type | Screw terminal |
| Time Interval | 0,2,5,10,15,20,25,30 adjustable |
| Integrated Buttons | 4 (Horn, Ack, Delete, Test) |
| Siren | + |
| Real Time Data Recording | 6080 logs |
| Battery Life | > 5 years |
| Protection Class | IP50 (front)IP20 (back) |
| Weight G | 280 |
| Packaging Quantity | 1 |
| Diagrams | --- |
| DIMENSIONS | --- |

| Power Supply | |
|--------------|----------------------------|
| Voltage | 110-300V AC/DC ±10% |

| | |
|-----------|----------------|
| Frequency | 45-65Hz |
|-----------|----------------|

Environmental Conditions

| | |
|----------------------------------|--------------------|
| Operating Temperature | -20°C +60°C |
| Storage Temperature | -30°C +80°C |
| Relative Humidity Non Condensing | Maks. 90% |

Communication

| | |
|-----------|-------------------|
| Protocol | Modbus RTU |
| Baud Rate | 1200-57600 |
| Parity | |
| Stop Bit | |
| Slave Id | |
| Isolation | 2500Vrms |

Input Signal

| | |
|---------------|---------------------|
| Voltage | 110V AC / DC |
| Frequency | 45-65Hz |
| Quantity | 8 |
| Response Time | 25±10ms |

Output Connections

| | |
|-----------------------------------|------------------------------------|
| Output Type | Relay |
| Number of Connections | 8 |
| Type | 1 NO (SPST) |
| Max Values Ac | 5A/277V;1385VA |
| Max Values Dc | 5A/30VDC;150W |
| Mechanical Operating Life | =10⁸ operation |
| Electrical Operating Life No Side | 1x10⁵(5A@250VAC) |

Window

| | |
|----------|-------------------------------|
| Quantity | 8 |
| Color | Red / Green selectable |

| | |
|---------------|--------------------------------------------------------------------------------------------|
| Size Mm | 30.5 x 21.6 |
| Illumination | With 4 pcs. red leds or 4 pcs. green led |
| Fast Flashing | 180 Flash / Min |
| Slow Flashing | 60 Flash / Min. |
| Marking | Laser printed onto standart tracing paper, using templates provided bu Klemsan Inc. |

DIMENSIONS

| | |
|-----------------------------------|-------------|
| Frontoverall Dimensions Height Mm | 96,8 |
| Frontoverall Dimensions Width Mm | 96,8 |
| Panel Cutout Dimensions Height Mm | 89,6 |
| Panel Cutout Dimensions Width Mm | 89,6 |
| Panel Cutout Dimensions Depth Mm | 65 |