



TERMINAL BLOCKS > BOLT TYPE TERMINAL BLOCKS > GROUNDING TERMINALS

## APP/PB 2,5-PB6/NM Grey

Stock Keeping Unit (SKU): 337010

Seperation Plate

### Commercial Information

Product Sales Code	<b>337010</b>
Package Unit	<b>45 pcs.</b>
Customs Tariff Number	<b>853690950000</b>
Weight Per Unit Including Packaging	<b>0.03 kg.</b>

### Technical Information

#### PRODUCT FEATURES

Number of Connections	<b>2</b>
Color	<b>Yellow/Green</b>
Number of Levels	<b>1</b>
Protective Conductor Type	<b>PE</b>
Insulation Material	<b>PA</b>
UL 94 Flammability Class	<b>V0</b>
Impulse Voltage Category	<b>III</b>
Insulation Material Group	<b>I</b>
Pollution Degree	<b>3</b>
Connection According to Standard	<b>IEC 60947-7-2</b>
Continuous Operating Temperature max.	<b>130 °C</b>
Continuous Operating Temperature min.	<b>-60 °C</b>

#### ELECTRICAL FEATURES

Nominal Impulse Voltage	<b>8 Kv</b>
-------------------------	-------------

## CONNECTION DATA

Connection Type	<b>Bolt Connection</b>
Single-core min. conductor cross-section	<b>0,1 mm<sup>2</sup></b>
Single-core max. conductor cross-section	<b>2,5 mm<sup>2</sup></b>
Conductor Cross Section Awgkcmil Min	<b>26 AWG</b>
Conductor Cross Section Awgkcmil Max	<b>14 AWG</b>
Multi-core min. conductor cross-section	<b>0,1 mm<sup>2</sup></b>
Multi-core max. conductor cross-section	<b>2,5 mm<sup>2</sup></b>
Tightening Torque Min	<b>0,6 Nm</b>
Tightening Torque Max	<b>0,8 Nm</b>
Hole Diameter Min	<b>3,2 mm</b>
Rail Tightening Torque Min	<b>0,4 Nm</b>
Rail Tightening Torque Max	<b>0,6 Nm</b>

## DIMENSIONS

Width	<b>10,00 mm</b>
Length	<b>44,70 mm</b>
Height Mr 35X75	<b>47,30 mm</b>
Height MR 35x15	<b>54,80 mm</b>
Height Mr 32	<b>51,90 mm</b>