

TERMINAL BLOCKS > SCREW TYPE TERMINAL BLOCKS > FUSE TERMINALS

ASK 2B

Stock Keeping Unit (SKU): 360119

Screw Type, 6 mm², fuse terminal block

Commercial Information

Product Sales Code	**360119**
Package Unit	**25 pcs.**
Customs Tariff Number	**853690950000**
Weight Per Unit Including Packaging	**0.02216 kg.**

Technical Information

PRODUCT SPECIFICATIONS	
Number of Connections	**2**
Color	**Grey**
Number of Levels	**1**
Insulation Material	**PA**
UL 94 Flammability Class	**V2**
Impulse Voltage Category	**III**
Insulation Material Group	**I**
Pollution Degree	**3**
Connection According to Standard	**IEC 60947-7-3**
Continuous Operating Temperature Max.	**120 °C**
Continuous Operating Temperature Min.	**-55 °C**

ELECTRICAL SPECIFICATIONS	
Nominal Current	**6.3 A**
Nominal Voltage	**24 V**

CONNECTION DATA	
Connection Type	**Screw Connection**
Min. Solid Conductor Cross-Sectional Area	**0.2 mm²**
Max. Solid Conductor Cross-Sectional Area	**10 mm²**
Conductor Cross-Section AWG/kcmil Min.	**24 AWG**
Conductor Cross-Section AWG/kcmil Max.	**8 AWG**
Min. Stranded Conductor Cross-Sectional Area	**0.2 mm²**
Max. Stranded Conductor Cross-Sectional Area	**10 mm²**
Min. Stranded Conductor Cross-Sectional Area with Ferrule	**0,25 mm²**
Max. Stranded Conductor Cross-Sectional Area with Ferrule	**6 mm²**
Min. for 2 Stranded Conductors of the Same Cross-Section with Plastic-Collared Twin Ferrule	**0,5 mm²**
Max. for 2 Stranded Conductors of the Same Cross-Section with Plastic-Collared Twin Ferrule	**4 mm²**
Min. Stripping Length	**10 mm**
Max. Stripping Length	**12 mm**
Internal Cylindrical Indicator	**B5**
Tightening Torque Min.	**0.8 Nm**
Tightening Torque Max.	**1.2 Nm**

DIMENSIONS	
Width	**8 mm**
Length	**64.2 mm**
Height MR 35x7.5	**45 mm**
Height MR 35x15	**52.5 mm**
Height MR 32	**49.6 mm**

Certificates

UL | VDE | CE | EAC | ROHS | UKCA

UL	
Conductor Cross-section	AWG 26-8
Nominal Current	6,3 A
Nominal Voltage	300 V

Accessories

END STOP



Product Code: 495049
KD 3 Grey



Product Code: 495059
KD 4 Grey



Product Code: 495219
KD 7 Grey

ZINC COATED



Product Code: 500601
MR 35x7.5 Straight (1m) Zinc Coated Rail



Product Code: 500604
MR 35x7.5 Slotted DIN Rail (2 m), Galvanized



Product Code: 500609
MR 35x15 Slotted (2m) Zinc Coated Rail



Product Code: 500602
MR 35x7.5 Slotted (1m) Zinc Coated Rail



Product Code: 500603
MR 35x7.5 Straight (2m) Zinc Coated Rail



Product Code: 500606
MR 35x15 Straight (1m) Zinc Coated Rail



Product Code: 500608

MR 35x15 Straight (2m) Zinc Coated Rail

ÇINKO KAPLI



Product Code: 500607

MR 35x15 Slotlu (1m) Çinko Kaplı Ray

GALVANIZED



Product Code: 500602E

MR 35x7.5 Slotted (1m) Rail (Galvanized)



Product Code: 500603E

MR 35x7,5 Plain (2m) Rail (Galvanized)



Product Code: 500604E

MR 35x7,5 SLOT (2m) RAIL (GALVANIZED)



Product Code: 500609E

MR 35x15 Slotted (2m) Rail (Galvanized)

SCREWDRIVERS



Product Code: 561230

IKT-D 3 (0,6 x Ø3,5)

TERMINAL THERMAL PRINTER LABELS



Product Code: 810300

D-NS 5x6

TERMINAL BLOCKS

Product Code: 505330

DG 6/5

END PLATE/COVER

Product Code: 450040

NPP/ASK 2 Beige



Product Code: 450049

NPP/ASK 2 Grey