

TERMINAL BLOCKS &gt; SCREW TYPE TERMINAL BLOCKS &gt; FUSE TERMINALS

## ASK 2LD-24VAC

**Stock Keeping Unit (SKU):** 351319*Screw Type, 6 mm<sup>2</sup>, fuse terminal block with LED*

### Commercial Information

Product Sales Code	<b>351319</b>
Package Unit	<b>25 pcs.</b>
Customs Tariff Number	<b>853690950000</b>
Weight Per Unit Including Packaging	<b>0.01896 kg.</b>

### Technical Information

#### PRODUCT FEATURES

Number of Connections	<b>2</b>
Color	<b>Grey</b>
Number of Levels	<b>1</b>
Insulation Material	<b>PA</b>
UL 94 Flammability Class	<b>V2</b>
Impulse Voltage Category	<b>III</b>
Insulation Material Group	<b>I</b>
Pollution Degree	<b>3</b>
Connection According to Standard	<b>IEC 60947-7-3</b>
Continuous Operating Temperature max.	<b>120 °C</b>
Continuous Operating Temperature min.	<b>-55 °C</b>
Fuse	<b>G / 5x20 - 5x25</b>
Fuse Type	<b>Cam / Glass</b>

#### ELECTRICAL FEATURES

Nominal Current	<b>6.3 A</b>
Nominal Voltage	<b>48 V</b>

## CONNECTION DATA

Connection Type	<b>Screw Connection</b>
Single-core min. conductor cross-section	<b>0.2 mm<sup>2</sup></b>
Single-core max. conductor cross-section	<b>10 mm<sup>2</sup></b>
Conductor Cross Section Awgkcmil Min	<b>24 AWG</b>
Conductor Cross Section Awgkcmil Max	<b>8 AWG</b>
Multi-core min. conductor cross-section	<b>0.2 mm<sup>2</sup></b>
Multi-core max. conductor cross-section	<b>10 mm<sup>2</sup></b>
Multi-core min. conductor cross-section with ferrule	<b>0,25 mm<sup>2</sup></b>
Multi-core max. conductor cross-section with ferrule	<b>6 mm<sup>2</sup></b>
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min	<b>0,5 mm<sup>2</sup></b>
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max	<b>4 mm<sup>2</sup></b>
Min. Stripping Length	<b>10 mm</b>
Max. Stripping Length	<b>12 mm</b>
Internal cylindrical indicator	<b>B5</b>
Tightening Torque Min	<b>0.8 Nm</b>
Tightening Torque Max	<b>1.2 Nm</b>

## DIMENSIONS

Width	<b>8 mm</b>
Length	<b>64.2 mm</b>
Height Mr 35X75	<b>45 mm</b>
Height MR 35x15	<b>52.5 mm</b>
Height Mr 32	<b>49.6 mm</b>