



TERMINAL BLOCKS > SCREW TYPE TERMINAL BLOCKS > FUSE TERMINALS

ASK 4LD-110VAC Grey

Stock Keeping Unit (SKU): 351759

Screw Type, 6 mm², fuse terminal block with LED

Commercial Information

| | |
|-------------------------------------|---------------------|
| Product Sales Code | 351759 |
| Package Unit | 20 pcs. |
| Customs Tariff Number | 853690950000 |
| Weight Per Unit Including Packaging | 0.029 kg. |

Technical Information

| PRODUCT FEATURES | |
|---------------------------------------|-------------------------|
| Number of Connections | 2 |
| Color | Grey |
| Number of Levels | 1 |
| Insulation Material | PA |
| UL 94 Flammability Class | V2 |
| Impulse Voltage Category | III |
| Insulation Material Group | I |
| Pollution Degree | 3 |
| Connection According to Standard | IEC 60947-7-3 |
| Continuous Operating Temperature max. | 120 °C |
| Continuous Operating Temperature min. | -55 °C |
| Fuse | G / 6,35 x 31,75 |
| Fuse Type | Cam / Glass |

ELECTRICAL FEATURES

| | |
|-----------------|--------------|
| Nominal Current | 6,3 A |
| Nominal Voltage | 110 V |

CONNECTION DATA

| | |
|--|----------------------------|
| Connection Type | Screw Connection |
| Single-core min. conductor cross-section | 0,34 mm² |
| Single-core max. conductor cross-section | 10 mm² |
| Conductor Cross Section Awgkcmil Min | 22 AWG |
| Conductor Cross Section Awgkcmil Max | 8 AWG |
| Multi-core min. conductor cross-section | 0,34 mm² |
| Multi-core max. conductor cross-section | 10 mm² |
| Multi-core min. conductor cross-section with ferrule | 0,25 mm² |
| Multi-core max. conductor cross-section with ferrule | 6 mm² |
| 2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min | 0,5 mm² |
| 2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max | 4 mm² |
| Min. Stripping Length | 9 mm |
| Max. Stripping Length | 10 mm |
| Internal cylindrical indicator | B5 |
| Tightening Torque Min | 0,5 Nm |
| Tightening Torque Max | 0,8 Nm |

DIMENSIONS

| | |
|-----------------|-----------------|
| Width | 10 mm |
| Length | 75,20 mm |
| Height Mr 35X75 | 52,40 mm |
| Height MR 35x15 | 59,90 mm |