


TERMINAL BLOCKS > SCREW TYPE TERMINAL BLOCKS > FEED THROUGH
TERMINALS



AVK 16 RD Blue

Stock Keeping Unit (SKU): 304241

16mm² Screw Type Transition Terminal

Commercial Information

Product Sales Code	304241
Package Unit	50 pcs.
Customs Tariff Number	853690950000
Weight Per Unit Including Packaging	0.03176 kg.

Technical Information

PRODUCT FEATURES	
Number of Connections	2
Color	Mavi
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V2
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-1
Continuous Operating Temperature max.	120 °C
Continuous Operating Temperature min.	-55 °C
ELECTRICAL FEATURES	
Nominal Impulse Voltage	8 Kv

Nominal Current	76 A
Nominal Voltage	1000 V
Maximum Load Current	101 A

CONNECTION DATA

Connection Type	Vidali Baglanti
Single-core min. conductor cross-section	1,5 mm²
Single-core max. conductor cross-section	25 mm²
Conductor Cross Section Awgkcmil Min	16 AWG
Conductor Cross Section Awgkcmil Max	4 AWG
Multi-core min. conductor cross-section	1,5 mm²
Multi-core max. conductor cross-section	25 mm²
Multi-core min. conductor cross-section with ferrule	1,5 mm²
Multi-core max. conductor cross-section with ferrule	16 mm²
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min	0,75 mm²
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max	10 mm²
Min. Stripping Length	12 mm
Max. Stripping Length	14 mm
Internal cylindrical indicator	B7
Tightening Torque Min	1,2 Nm
Tightening Torque Max	2 Nm

DIMENSIONS

Width	12 mm
Length	52,80 mm
Height Mr 35X75	58,60 mm
Height MR 35x15	63,20 mm