


TERMINAL BLOCKS > SCREW TYPE TERMINAL BLOCKS > GROUNDING TERMINALS



AVK 70-95T Yellow-Green

Stock Keeping Unit (SKU): 336660

Screw Type Terminal

Commercial Information

Product Sales Code	336660
Package Unit	6 pcs.
Customs Tariff Number	853690950000
Weight Per Unit Including Packaging	0.25333 kg.

Technical Information

PRODUCT FEATURES	
Number of Connections	2
Color	Yellow/Green
Number of Levels	1
Protective Conductor Type	PE
Insulation Material	PA
UL 94 Flammability Class	V2
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Protective Conductor Type	PE
Connection According to Standard	IEC 60947-7-2
Continuous Operating Temperature max.	120 °C
Continuous Operating Temperature min.	-55 °C
Note	DIN raylarının akım tasama kapasitesine dikkat edilmelidir. / Observe the current carrying capacity of the DIN rails.

ELECTRICAL FEATURES

Nominal Impulse Voltage	8 Kv
-------------------------	-------------

CONNECTION DATA

Connection Type	Screw Connection
-----------------	-------------------------

Single-core min. conductor cross-section	25 mm²
--	--------------------------

Single-core max. conductor cross-section	95 mm²
--	--------------------------

Conductor Cross Section Awgkcmil Min	4 AWG
--------------------------------------	--------------

Conductor Cross Section Awgkcmil Max	3/0 AWG
--------------------------------------	----------------

Multi-core min. conductor cross-section	35 mm²
---	--------------------------

Multi-core max. conductor cross-section	95 mm²
---	--------------------------

Multi-core min. conductor cross-section with ferrule	35 mm²
--	--------------------------

Multi-core max. conductor cross-section with ferrule	95 mm²
--	--------------------------

2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min	16 mm²
--	--------------------------

2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max	35 mm²
--	--------------------------

Min. Stripping Length	26 mm
-----------------------	--------------

Max. Stripping Length	28 mm
-----------------------	--------------

Internal cylindrical indicator	B12
--------------------------------	------------

Tightening Torque Min	10 Nm
-----------------------	--------------

Tightening Torque Max	15 Nm
-----------------------	--------------

Rail Tightening Torque Min	3 Nm
----------------------------	-------------

Rail Tightening Torque Max	6 Nm
----------------------------	-------------

DIMENSIONS

Width	25 mm
-------	--------------

Length	80 mm
--------	--------------

Height MR 35x15	98,10 mm
-----------------	-----------------

Height Mr 32	95,20 mm
--------------	-----------------