


TERMINAL BLOCKS > SCREW TYPE TERMINAL BLOCKS > FEED THROUGH
TERMINALS



AYK 10/16 4 Lü Beige

Stock Keeping Unit (SKU): 395240

10mm² - 16mm² Screw-Type Feed-Through Terminal Block - 4

Commercial Information

Product Sales Code	395240
Package Unit	20 pcs.
Customs Tariff Number	853690950000
Weight Per Unit Including Packaging	0.1884 kg.

Technical Information

PRODUCT FEATURES

Number of Connections	4
Color	Beige
Number of Levels	4
Insulation Material	PA
UL 94 Flammability Class	V2
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-1
Continuous Operating Temperature max.	120 °C
Continuous Operating Temperature min.	-55 °C

ELECTRICAL FEATURES

Nominal Impulse Voltage	8 Kv
Nominal Current	76 A
Nominal Voltage	750 V
Maximum Load Current	76 A

CONNECTION DATA

Connection Type	Screw Connection
Single-core min. conductor cross-section	2.5mm² / 0.5mm² mm²
Single-core max. conductor cross-section	25mm² / 16mm² mm²
Conductor Cross Section Awgkcmil Min	14 AWG / 20 AWG AWG
Conductor Cross Section Awgkcmil Max	4 AWG / 6 AWG AWG
Multi-core min. conductor cross-section	4mm² / 0.5mm² mm²
Multi-core max. conductor cross-section	25mm² / 16mm² mm²
Multi-core min. conductor cross-section with ferrule	2.5mm² / 0.5mm² mm²
Multi-core max. conductor cross-section with ferrule	16mm² / 10mm² mm²
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min	1.5mm² / 0.5mm² mm²
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max	10mm² / 6mm² mm²
Min. Stripping Length	14mm / 8mm mm
Max. Stripping Length	16mm / 10mm mm
Internal cylindrical indicator	B6
Tightening Torque Min	1.2Nm / 1.2Nm Nm
Tightening Torque Max	2.0Nm / 1.8Nm Nm

DIMENSIONS

Width	11 mm
Length	69,5 mm
Height Mr 35X75	653 mm
Height MR 35x15	72,80 mm
Height Mr 32	69,9 mm