

TERMINAL BLOCKS > OTHER PRODUCTS > BUSBAR TERMINALS



## BKN 4

**Stock Keeping Unit (SKU):** 525410

*4 mm<sup>2</sup> Clamping Yokes for Busbars*

### Commercial Information

|                                     |                     |
|-------------------------------------|---------------------|
| Product Sales Code                  | <b>525410</b>       |
| Package Unit                        | <b>50 pcs.</b>      |
| Customs Tariff Number               | <b>853690950000</b> |
| Weight Per Unit Including Packaging | <b>0.00496 kg.</b>  |

### Technical Information

#### PRODUCT FEATURES

|          |                  |
|----------|------------------|
| Material | <b>Steel</b>     |
| Coating  | <b>Zn (Cr+3)</b> |

#### ELECTRICAL FEATURES

|                      |             |
|----------------------|-------------|
| Nominal Current      | <b>32 A</b> |
| Maximum Load Current | <b>41 A</b> |

#### CONNECTION DATA

|  |                           |
|--|---------------------------|
| Connection Type                          | <b>Screw Connection</b>   |
| Single-core min. conductor cross-section | <b>0,5 mm<sup>2</sup></b> |
| Single-core max. conductor cross-section | <b>6 mm<sup>2</sup></b>   |
| Conductor Cross Section Awgkcmil Min     | <b>20 AWG</b>             |
| Conductor Cross Section Awgkcmil Max     | <b>10 AWG</b>             |
| Multi-core min. conductor cross-section  | <b>0,5 mm<sup>2</sup></b> |
| Multi-core max. conductor cross-section  | <b>6 mm<sup>2</sup></b>   |

|  |                           |
|--|---------------------------|
| Multi-core min. conductor cross-section with ferrule                                   | <b>0,5 mm<sup>2</sup></b> |
| Multi-core max. conductor cross-section with ferrule                                   | <b>4 mm<sup>2</sup></b>   |
| 2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min | <b>0,5 mm<sup>2</sup></b> |
| 2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max | <b>2,5 mm<sup>2</sup></b> |
| Min. Stripping Length  | <b>16 mm</b>              |
| Tightening Torque Min  | <b>1,5 Nm</b>             |
| Tightening Torque Max  | <b>1,8 Nm</b>             |
| Busbar Size  | <b>3x12 mm</b>            |

## DIMENSIONS

|        |                 |
|--------|-----------------|
| Width  | <b>7,00 mm</b>  |
| Length | <b>25,00 mm</b> |