



TERMINAL BLOCKS > BOLT TYPE TERMINAL BLOCKS > FEED THROUGH TERMINALS

## CPB 6U Grey

**Stock Keeping Unit (SKU):** 326829

*Fork Type, 6 mm<sup>2</sup> Fork type lug connection*

### Commercial Information

|                                     |                     |
|-------------------------------------|---------------------|
| Product Sales Code                  | <b>326829</b>       |
| Package Unit                        | <b>25 pcs.</b>      |
| Customs Tariff Number               | <b>853690950000</b> |
| Weight Per Unit Including Packaging | <b>0.0168 kg.</b>   |

### Technical Information

| PRODUCT FEATURES                      |                      |
|---------------------------------------|----------------------|
| Number of Connections                 | <b>2</b>             |
| Color                                 | <b>Grey</b>          |
| Number of Levels                      | <b>1</b>             |
| Insulation Material                   | <b>PA</b>            |
| UL 94 Flammability Class              | <b>V2</b>            |
| Impulse Voltage Category              | <b>3</b>             |
| Insulation Material Group             | <b>1</b>             |
| Pollution Degree                      | <b>3</b>             |
| Connection According to Standard      | <b>IEC 60947-7-1</b> |
| Continuous Operating Temperature max. | <b>120 °C</b>        |
| Continuous Operating Temperature min. | <b>-55 °C</b>        |

| ELECTRICAL FEATURES     |             |
|-------------------------|-------------|
| Nominal Impulse Voltage | <b>8 Kv</b> |
| Nominal Current         | <b>57 A</b> |

|                 |              |
|-----------------|--------------|
| Nominal Voltage | <b>500 V</b> |
|-----------------|--------------|

## CONNECTION DATA

|  |                           |
|--|---------------------------|
| Connection Type                          | <b>Bolt Connection</b>    |
| Single-core min. conductor cross-section | <b>0,5 mm<sup>2</sup></b> |
| Single-core max. conductor cross-section | <b>10 mm<sup>2</sup></b>  |
| Conductor Cross Section Awgkcmil Min     | <b>20 AWG AWG</b>         |
| Conductor Cross Section Awgkcmil Max     | <b>8 AWG AWG</b>          |
| Multi-core min. conductor cross-section  | <b>0,5 mm<sup>2</sup></b> |
| Multi-core max. conductor cross-section  | <b>10 mm<sup>2</sup></b>  |
| Tightening Torque Min                    | <b>1,2 Nm</b>             |
| Tightening Torque Max                    | <b>1,8 Nm</b>             |

## DIMENSIONS

|                 |                 |
|-----------------|-----------------|
| Width           | <b>13,00 mm</b> |
| Length          | <b>42,60 mm</b> |
| Height Mr 35X75 | <b>46,50 mm</b> |
| Height MR 35x15 | <b>54,00 mm</b> |
| Height Mr 32    | <b>51,10 mm</b> |