

CONNECTORS > MIL-DTL-38999 > SERIES III

D38999/20WB5PE

Stock Keeping Unit (SKU): 930WB5PE

Wall mount flange type receptacle

Commercial Information

Product Sales Code	**930WB5PE**
Package Unit	**1 pcs.**

Technical Information

PRODUCT SPECIFICATIONS	
Continuous Operating Temperature Max.	**175 °C**
Continuous Operating Temperature Min.	**65 °C**
Features	**MIL-DTL-38999**
Connector Type	**Wall Mounted Socket**
Housing Size	**11 (B)**
Number of Contacts	**5 Ad.**
Layout	**B-5**
Housing Material	**Aluminium**
Housing Colour	**Khaki Green**
Housing Coating	**Cadmium**
Contact Type	**Pin (5#20)**
Cable Diameter	**24,22,20 AWG**
Contact Material	**Au/Cu**
Sealing Protection	**IP67**
Sealing Material	**Silicon**

EMI Shielding	**+**
Mating Cycle Life	**500**
Polarisation	**E**
Service Rating	**I**

ELECTRICAL SPECIFICATIONS	
Nominal Current	**7,5 A**
Operating Voltage (AC) Vrms (Max.)	**1800V AC/DC**

Accessories

CABLE TUBES

Product Code: 939BSB1

Straight Tube

Product Code: 939RSB1Y

90° Straight Tube

CONTACT

Product Code: M39029-58-363

M39029/58-363

CRIMPING TOOL



Product Code: M22520-1-01

M22520/1-01

LOCATOR

Product Code: M22520-1-04

M22520/1-04

INSERTION/EXTRACTION TOOL

Product Code: M81969-14-10

Takma / Insertion

Product Code: M81969-8-05

Takma / Insertion

Product Code: M81969-8-06

M81969/8-06

DUST CAP



Product Code: 933W11R

D38999/33W11R

BACKSHELL



Product Code: 939W881103

M85049/88-11W03



Product Code: 939UW11

Düz Arkalik



Product Code: 939UW11EMI

M85049/88D11W03

Product Code: M85049-38-11W

M85049/38-09W