

CONNECTORS > MIL-DTL-38999 > SERIES III



## D38999/20WB5SD

**Stock Keeping Unit (SKU):** 930WB5SD

*Wall mount flange type receptacle*

### Commercial Information

|                    |                 |
|--------------------|-----------------|
| Product Sales Code | <b>930WB5SD</b> |
| Package Unit       | <b>1 pcs.</b>   |

### Technical Information

| PRODUCT FEATURES                      |                            |
|---------------------------------------|----------------------------|
| Continuous Operating Temperature max. | <b>175 °C</b>              |
| Continuous Operating Temperature min. | <b>65 °C</b>               |
| Features                              | <b>MIL-DTL-38999</b>       |
| Connector Type                        | <b>Wall Mounted Socket</b> |
| Housing Size                          | <b>11 (B)</b>              |
| Number Of Contacts                    | <b>5 Ad.</b>               |
| Placement                             | <b>B-5</b>                 |
| Housing Material                      | <b>Aluminium</b>           |
| Housing Color                         | <b>Khaki Green</b>         |
| Housing Coating                       | <b>Cadmium</b>             |
| Contact Type                          | <b>Soket (5#20)</b>        |
| Wire Gauge                            | <b>24,22,20 AWG</b>        |
| Contact Material                      | <b>Au/Cu</b>               |
| Ingress Protection                    | <b>IP67</b>                |
| Sealing Material                      | <b>Silicon</b>             |

|                |            |
|----------------|------------|
| Emi Shielding  | <b>+</b>   |
| Mating Cycles  | <b>500</b> |
| Polarization   | <b>D</b>   |
| Service Rating | <b>I</b>   |

## ELECTRICAL FEATURES

|                                |                    |
|--------------------------------|--------------------|
| Nominal Current                | <b>7,5 A</b>       |
| Operating Voltage Ac V Rms Max | <b>1800V AC/DC</b> |