

CONNECTORS > MIL-DTL-38999 > SERIES III

D38999/20WD35PA

Stock Keeping Unit (SKU): 930WD35PA

Wall mount flange type receptacle

Commercial Information

Product Sales Code	**930WD35PA**
Package Unit	**1 pcs.**

Technical Information

PRODUCT SPECIFICATIONS	
Continuous Operating Temperature Max.	**175 °C**
Continuous Operating Temperature Min.	**65 °C**
Features	**MIL-DTL-38999**
Connector Type	**Wall Mounted Socket**
Housing Size	**15(D)**
Number of Contacts	**37 Ad.**
Layout	**D-35**
Housing Material	**Aluminium**
Housing Colour	**Khaki Green**
Housing Coating	**Cadmium**
Contact Type	**Pin (37#22)**
Cable Diameter	**28,26,24,22 AWG**
Contact Material	**Au/Cu**
Sealing Protection	**IP67**
Sealing Material	**Silicon**

EMI Shielding	**+**
Mating Cycle Life	**500**
Polarisation	**A**
Service Rating	**M**

ELECTRICAL SPECIFICATIONS	
Nominal Current	**5A A**
Operating Voltage (AC) Vrms (Max.)	**1300V AC/DC**

Accessories

INSERTION/EXTRACTION TOOL



Product Code: M81969-8-03

Takma / Insertion

Product Code: M81969-8-04

M81969-8-04

Product Code: M81969/14-01

M81969/14-01

CONTACT

Product Code: M39029-58-360

M39029/58-360

CRIMPING TOOL

Product Code: M22520-2-01

M22520/2-01

LOCATOR

Product Code: M22520-2-09

M22520/2-09

CABLE TUBES



Product Code: 939BSB2

Straight Tube



Product Code: 939RSB2Y

90° Straight Tube

BACKSHELL



Product Code: 939W881503

M85049/88-15W03



Product Code: 939UW15EMI

M85049/88D15W03



Product Code: 939UW15

Düz Arkalik



Product Code: M85049-38-15W

M85049/38-15W

DUST CAP



Product Code: 933W15R

D38999/33W15R