

CONNECTORS > MIL-DTL-38999 > SERIES III



D38999/20WF30PD

Stock Keeping Unit (SKU): 930WF30PD

Wall mount flange type receptacle

Commercial Information

| | |
|--------------------|------------------|
| Product Sales Code | 930WF30PD |
| Package Unit | 1 pcs. |

Technical Information

| PRODUCT FEATURES | |
|---------------------------------------|----------------------------|
| Continuous Operating Temperature max. | 175 °C |
| Continuous Operating Temperature min. | 65 °C |
| Features | MIL-DTL-38999 |
| Connector Type | Wall Mounted Socket |
| Housing Size | 19(F) |
| Number Of Contacts | 30 Ad. |
| Placement | F-30 |
| Housing Material | Aluminium |
| Housing Color | Khaki Green |
| Housing Coating | Cadmium |
| Contact Type | Pin (29#20) (1#16) |
| Wire Gauge | 24,22,20,18,16 AWG |
| Contact Material | Au/Cu |
| Ingress Protection | IP67 |
| Sealing Material | Silicon |

| | |
|----------------|------------|
| Emi Shielding | + |
| Mating Cycles | 500 |
| Polarization | D |
| Service Rating | I |

ELECTRICAL FEATURES

| | |
|--------------------------------|---------------------|
| Nominal Current | 7,5&13 A |
| Operating Voltage Ac V Rms Max | 1800V AC/DC |