

CONNECTORS > MIL-DTL-38999 > SERIES III

D38999/24WD5PD

Stock Keeping Unit (SKU): 934WD5PD

Wall mount flange type receptacle

Commercial Information

Product Sales Code	**934WD5PD**
Package Unit	**1 pcs.**

Technical Information

PRODUCT SPECIFICATIONS	
Continuous Operating Temperature Max.	**175 °C**
Continuous Operating Temperature Min.	**65 °C**
Features	**MIL-DTL-38999**
Connector Type	**Screwed Socket**
Housing Size	**15(D)**
Number of Contacts	**5 Ad.**
Layout	**D-5**
Housing Material	**Aluminium**
Housing Colour	**Khaki Green**
Housing Coating	**Cadmium**
Contact Type	**Pin (5#16)**
Cable Diameter	**20,18,16 AWG**
Contact Material	**Au/Cu**

Sealing Protection	**IP67**
Sealing Material	**Silicon**
EMI Shielding	**+**
Mating Cycle Life	**500**
Polarisation	**D**
Service Rating	**II**

ELECTRICAL SPECIFICATIONS	
Nominal Current	**13 A**
Operating Voltage (AC) Vrms (Max.)	**2300V AC/DC**

Accessories

CRIMPING TOOL



Product Code: M22520-1-01

M22520/1-01

LOCATOR

Product Code: M22520-1-04

M22520/1-04

CONTACT

Product Code: M39029-58-364

M39029/58-364

INSERTION/EXTRACTION TOOL

Product Code: M81969-8-07

M81969-8-07

Product Code: M81969-8-08

M81969-8-08

Product Code: M81969-14-03

M81969-14-03

CABLE TUBES



Product Code: 939BSB2

Straight Tube



Product Code: 939RSB2Y

90° Straight Tube

BACKSHELL



Product Code: 939W881503

M85049/88-15W03



Product Code: 939UW15EMI

M85049/88D15W03



Product Code: 939UW15

Düz Arkalik



Product Code: M85049-38-15W

M85049/38-15W

DUST CAP



Product Code: 933W15N

D38999/33W15N