

CONNECTORS > MIL-DTL-38999 > SERIES III

D38999/24WF32SE

Stock Keeping Unit (SKU): 934WF32SE

Wall maunt jamnut receptacle

Commercial Information

Product Sales Code	**934WF32SE**
Package Unit	**1 pcs.**

Technical Information

PRODUCT SPECIFICATIONS	
Continuous Operating Temperature Max.	**175 °C**
Continuous Operating Temperature Min.	**65 °C**
Features	**MIL-DTL-38999**
Connector Type	**Screwed Socket**
Housing Size	**19(F)**
Number of Contacts	**32 Ad.**
Layout	**F-32**
Housing Material	**Aluminium**
Housing Colour	**Khaki Green**
Housing Coating	**Cadmium**
Contact Type	**Soket (32#20)**
Cable Diameter	**24,22,20 AWG**
Contact Material	**Au/Cu**

Sealing Protection	**IP67**
Sealing Material	**Silicon**
EMI Shielding	**+**
Mating Cycle Life	**500**
Polarisation	**D**
Service Rating	**I**

ELECTRICAL SPECIFICATIONS	
Nominal Current	**7,5&13 A**
Operating Voltage (AC) Vrms (Max.)	**1800V AC/DC**

Accessories

CRIMPING TOOL



Product Code: M22520-1-01

M22520/1-01

LOCATOR

Product Code: M22520-1-04

M22520/1-04

INSERTION/EXTRACTION TOOL

Product Code: M81969-14-10

Takma / Insertion

Product Code: M81969-8-05

Takma / Insertion

Product Code: M81969-8-06

M81969/8-06

CABLE TUBES



Product Code: 939BSB3

Straight Tube



Product Code: 939RSB3Y

90° Tube

BACKSHELL



Product Code: 939W881903

M85049/88-19W03



Product Code: 939UW19EMI

M85049/88D19W03



Product Code: 939UW19

Düz Arkalik



Product Code: M85049-38-19W

M85049/38-19W

CONTACT



Product Code: M39029-56-351

M39029/56-351