

CONNECTORS > MIL-DTL-38999 > SERIES III



D38999/24WG16SD

Stock Keeping Unit (SKU): 934WG16SD

Wall maunt jamnut receptacle

Commercial Information

| | |
|--------------------|------------------|
| Product Sales Code | 934WG16SD |
| Package Unit | 1 pcs. |

Technical Information

| PRODUCT FEATURES | |
|---------------------------------------|-----------------------|
| Continuous Operating Temperature max. | 175 °C |
| Continuous Operating Temperature min. | 65 °C |
| Features | MIL-DTL-38999 |
| Connector Type | Screwed Socket |
| Housing Size | 21(G) |
| Number Of Contacts | 16 Ad. |
| Placement | G-16 |
| Housing Material | Aluminium |
| Housing Color | Khaki Green |
| Housing Coating | Cadmium |
| Contact Type | Soket (16#16) |
| Wire Gauge | 20,18,16 AWG |
| Contact Material | Au/Cu |

| | |
|--------------------|----------------|
| Ingress Protection | IP67 |
| Sealing Material | Silicon |
| Emi Shielding | + |
| Mating Cycles | 500 |
| Polarization | D |
| Service Rating | II |

ELECTRICAL FEATURES

| | |
|--------------------------------|--------------------|
| Nominal Current | 13 A |
| Operating Voltage Ac V Rms Max | 2300V AC/DC |