

CONNECTORS > MIL-DTL-38999 > SERIES III

D38999/26WD19SD

Stock Keeping Unit (SKU): 936WD19SD

Cable type connector

Commercial Information

Product Sales Code	**936WD19SD**
Package Unit	**1 pcs.**

Technical Information

PRODUCT SPECIFICATIONS	
Continuous Operating Temperature Max.	**175 °C**
Continuous Operating Temperature Min.	**65 °C**
Features	**MIL-DTL-38999**
Connector Type	**Plug**
Housing Size	**15(D)**
Number of Contacts	**19 Ad.**
Layout	**D-19**
Housing Material	**Aluminium**
Housing Colour	**Khaki Green**
Housing Coating	**Cadmium**
Contact Type	**Soket (19#20)**
Cable Diameter	**24,22,20, AWG**
Contact Material	**Au/Cu**

Sealing Protection	**IP67**
Sealing Material	**Silicon**
EMI Shielding	**+**
Mating Cycle Life	**500**
Polarisation	**D**
Service Rating	**I**

ELECTRICAL SPECIFICATIONS	
Nominal Current	**7,5A A**
Operating Voltage (AC) Vrms (Max.)	**1800V AC/DC**

Accessories

CRIMPING TOOL



Product Code: M22520-1-01

M22520/1-01

LOCATOR

Product Code: M22520-1-04

M22520/1-04

INSERTION/EXTRACTION TOOL

Product Code: M81969-14-10

Takma / Insertion

Product Code: M81969-8-05

Takma / Insertion

Product Code: M81969-8-06

M81969/8-06

CABLE TUBES



Product Code: 939BSB2

Straight Tube



Product Code: 939RSB2Y

90° Straight Tube

BACKSHELL



Product Code: 939W881503

M85049/88-15W03



Product Code: 939UW15EMI

M85049/88D15W03



Product Code: 939UW15

Düz Arkalik



Product Code: M85049-38-15W

M85049/38-15W

CONTACT

Product Code: M39029-56-351

M39029/56-351

DUST CAP



Product Code: 932W15N

D38999/32W15N



Product Code: 932W15R

D38999/32W15R