



| Gövde | A (maks) | B Diğ | C (maks) |
|-------|----------|----------|----------|
| 09 | 31.00 | M12*1-6g | 21.80 |
| 11 | 31.00 | M12*1-6g | 23.50 |
| 13 | 31.00 | M18*1-6g | 29.40 |
| 15 | 31.00 | M22*1-6g | 32.40 |
| 17 | 31.00 | M25*1-6g | 35.60 |
| 19 | 31.00 | M28*1-6g | 38.50 |
| 21 | 31.00 | M31*1-6g | 41.70 |
| 23 | 31.00 | M34*1-6g | 44.50 |
| 25 | 31.00 | M37*1-6g | 48.00 |

CONNECTORS > MIL-DTL-38999 > SERIES III

D38999/26WJ11SB

Stock Keeping Unit (SKU): 936WJ11SB

Cable type connector

Commercial Information

| | |
|--------------------|------------------|
| Product Sales Code | 936WJ11SB |
| Package Unit | 1 pcs. |

Technical Information

| PRODUCT FEATURES | |
|---------------------------------------|-----------------------------|
| Continuous Operating Temperature max. | 175 °C |
| Continuous Operating Temperature min. | 65 °C |
| Features | MIL-DTL-38999 |
| Connector Type | Plug |
| Housing Size | 25(J) |
| Number Of Contacts | 11 Ad. |
| Placement | j-11 |
| Housing Material | Aluminium |
| Housing Color | Khaki Green |
| Housing Coating | Cadmium |
| Contact Type | Socket (2#20) (9#10) |
| Wire Gauge | 24,22,20 AWG |
| Contact Material | Au/Cu |
| Ingress Protection | IP67 |
| Sealing Material | Silicon |
| Emi Shielding | + |

| | |
|----------------|------------|
| Mating Cycles | 500 |
| Polarization | B |
| Service Rating | I |

ELECTRICAL FEATURES

| | |
|--------------------------------|--------------------|
| Nominal Current | 7,5 A |
| Operating Voltage Ac V Rms Max | 1300V AC/DC |