



Gövde	A (maks)	B Diğ	C (maks)
09	31.00	M12*1-6g	21.80
11	31.00	M12*1-6g	23.50
13	31.00	M18*1-6g	29.40
15	31.00	M22*1-6g	32.40
17	31.00	M25*1-6g	35.60
19	31.00	M28*1-6g	38.50
21	31.00	M31*1-6g	41.70
23	31.00	M34*1-6g	44.50
25	31.00	M37*1-6g	48.00

CONNECTORS > MIL-DTL-38999 > SERIES III

D38999/26WJ20SN

Stock Keeping Unit (SKU): 936WJ20SN

Cable type connector

Commercial Information

Product Sales Code	936WJ20SN
Package Unit	1 pcs.

Technical Information

PRODUCT FEATURES	
Continuous Operating Temperature max.	175 °C
Continuous Operating Temperature min.	65 °C
Features	MIL-DTL-38999
Connector Type	Plug
Housing Size	25(J)
Number Of Contacts	30 Ad.
Placement	j-20
Housing Material	Aluminium
Housing Color	Khaki Green
Housing Coating	Cadmium
Contact Type	Socket (10#20) (13#16) (3#8 Twinax) (4#12 Coax&Shielded)
Wire Gauge	24,22,20,18,16 AWG
Contact Material	Au/Cu
Ingress Protection	IP67
Sealing Material	Silicon
Emi Shielding	+

Mating Cycles	500
Polarization	N
Service Rating	I

ELECTRICAL FEATURES

Nominal Current	7,5-13 A
Operating Voltage Ac V Rms Max	1800V AC/DC
