



Gövde	A (maks)	B Diğ	C (maks)
09	31.00	M12*1-6g	21.80
11	31.00	M12*1-6g	23.50
13	31.00	M18*1-6g	29.40
15	31.00	M22*1-6g	32.40
17	31.00	M25*1-6g	35.60
19	31.00	M28*1-6g	38.50
21	31.00	M31*1-6g	41.70
23	31.00	M34*1-6g	44.50
25	31.00	M37*1-6g	48.00

CONNECTORS > MIL-DTL-38999 > SERIES III

## D38999/26WJ29SB

Stock Keeping Unit (SKU): 936WJ29SB

Cable type connector

### Commercial Information

Product Sales Code	<b>936WJ29SB</b>
Package Unit	<b>1 pcs.</b>

### Technical Information

PRODUCT FEATURES	
Continuous Operating Temperature max.	<b>175 °C</b>
Continuous Operating Temperature min.	<b>65 °C</b>
Features	<b>MIL-DTL-38999</b>
Connector Type	<b>Plug</b>
Housing Size	<b>25(J)</b>
Number Of Contacts	<b>29 Ad.</b>
Placement	<b>j-29</b>
Housing Material	<b>Aluminium</b>
Housing Color	<b>Khaki Green</b>
Housing Coating	<b>Cadmium</b>
Contact Type	<b>Soket (29#16)</b>
Wire Gauge	<b>20,18,16 AWG</b>
Contact Material	<b>Au/Cu</b>
Ingress Protection	<b>IP67</b>
Sealing Material	<b>Silicon</b>
Emi Shielding	<b>+</b>

Mating Cycles	<b>500</b>
Polarization	<b>B</b>
Service Rating	<b>I</b>

## ELECTRICAL FEATURES

Nominal Current	<b>13 A</b>
Operating Voltage Ac V Rms Max	<b>1800V AC/DC</b>