

ELECTRONICS PRODUCTS > PROTECTION CONTROL & TIME RELAYS > DIGITAL
PROTECTION RELAY

DPR 3120

Stock Keeping Unit (SKU): 270601*Digital Protection Relay*

Commercial Information

Product Sales Code	270601
Package Unit	1 pcs.
Customs Tariff Number	853649000029
Weight Per Unit Including Packaging	0.1376 kg.

Technical Information

General

Protection Class	IP20
Packaging Quantity	1
Supply Frequency	35-70Hz
Output Type	Relay

Power Supply

Voltage	85..300 V AC
Frequency	35-70Hz
Power Consumption	<4VA, <4VA AC

Environmental Conditions

Operating Temperature	-20°C..+70 °C
Storage Temperature	-30°C..+80 °C
Relative Humidity Non Condensing	90% non-condensing

Relay Output

Number Of Outputs	2
Max Switching Current	10A / 250VAC
Max Switching Power	1250VA
Type	2 C/O (SPDT)
Electrical Life	5x10⁴
Mechanical Life	= 10⁷

Monitoring Functions

Phase Loss Delay Time	0 - 999 ms
Phase Sequence Delay Time	0 - 999 ms
Voltage Protection Lower Limit	0 - 999 V
Voltage Protection Hysteresis	0 - 999 V
Voltage Protection Delay Time	0 - 999 sn
Ptc Protection High Value Threshold	-- Ohm
Ptc Protection Delay Time	-- sn