

ELECTRONICS PRODUCTS > COMMUNICATION INTERFACES > GATEWAY



## ETOR-4

**Stock Keeping Unit (SKU):** 601400

*Ethernet Gateway (TCP/IP - RS485)*

### Commercial Information

Product Sales Code	<b>601400</b>
Package Unit	<b>1 pcs.</b>
Weight Per Unit Including Packaging	<b>58 kg.</b>

### Technical Information

#### CONNECTION DATA

Connection Type	<b>Screw Terminal (for supply and serial interface)</b>
-----------------	---

#### General

Case Width Mm	<b>17,5</b>
Operating Mode	<b>Server or Client Selectable (bidirectional)</b>
Configuration	<b>Mini USB Port or Web Interface</b>
Dhcp Automatic Ip Acquisition	<b>+</b>
Arp	<b>+</b>
Ping Blocking	<b>+</b>
Led Indicators	<b>+</b>
Reset Function	<b>+</b>
Esd Protection	<b>+</b>
Supported Drivers	<b>Microsoft .NET Framework 3.5 üzeri windows işletim sistemleri</b>

#### Power Supply

Voltage	<b>18-50V AC / 18-50V DC</b>
Frequency	<b>45-65Hz</b>
Consumption	<b>&lt; 2,2 VA AC / &lt; 1 W DC</b>

### Mechanical Properties

Weight G	<b>58</b>
Protection Class	<b>IP20</b>
Mounting Type	<b>Rail Mount</b>
Packaging Quantity	<b>1</b>

### Environmental Conditions

Operating Temperature	<b>-10°C +60°C</b>
Storage Temperature	<b>-30°C +80°C</b>
Relative Humidity Non Condensing	<b>Max. 95%</b>

### Emc Emi

Compliance With Ts En 55022 Ts En 55024	
---	--

### Galvanic Isolation

Power Supply Ethernet Port	<b>1500VRMS, 2250VDC</b>
Power Supply Serial Port	<b>1500VRMS, 2250VDC</b>
Serial Port Ethernet Port	<b>2500VRMS</b>

### Ethernet Interface

Number Of Ports	<b>1</b>
Operating Modes	<b>Modbus TCP, Modbus RTU over TCP, Modbus ASCII over TCP</b>
Server Mode	<b>6</b>
Receiver Mode	<b>1</b>
Connector	<b>RJ45</b>
Data Transfer Rate	<b>10/100 Base-TX</b>

### Serial Interface

Number Of Ports	<b>1</b>
Operating Modes	<b>Modbus RTU, Modbus ASCII</b>

Serial Connection Standard	<b>RS485</b>
Server Mode	<b>64</b>
Receiver Mode	<b>1</b>
Baud Rate	<b>300 to 115200 bps</b>
Data Bits	<b>8</b>
Stop Bits	<b>1 or 2</b>
Parity	<b>None, Even, Odd</b>

---