

ELECTRONICS PRODUCTS > PROTECTION CONTROL & TIME RELAYS > GENERAL
MONITORING RELAYS

FK1T-P 24-265

Stock Keeping Unit (SKU): 270297

Motor Protection Relay



Commercial Information

Product Sales Code	270297
Package Unit	1 pcs.
Customs Tariff Number	853649000029
Weight Per Unit Including Packaging	0.08 kg.

Technical Information

PRODUCT FEATURES	
Connection Type	Screw terminal
Protection Class	IP20
Weight G	80
Packaging Quantity	1
Case Width Mm	18
Mounting Type	Rail Mount
Emc Emi	ok
Voltage	24-265 V DC / 24-265 V AC
Frequency	50-60Hz
Consumption	<13VA AC
Operating Temperature	-20 to +60°C
Storage Temperature	-40°C +75°C

Relative Humidity Non Condensing	Max. 95% (no condensation)
Type	1 C/O (SPDT)
Max Values Ac No Side	10A/250V; 1250 VA
Max Values Dc No Side	5A/30VDC; 150W
Mechanical Operating Life	= 10⁷ operations
Electrical Operating Life No Side	5x10⁴ (5A@250VAC) 1x10⁵ (5A@30VDC)
Phase Loss Delay Time	ms
Phase Sequence Delay Time	ms
Neutral Loss Delay Time	ms
Ptc Protection Short Circuit Threshold	20 ohm
Ptc Protection High Value Threshold	2.7 k ohm
Ptc Protection Delay Time	500ms