



ELECTRONICS PRODUCTS > PROTECTION CONTROL & TIME RELAYS > VOLTAGE MONITORING RELAYS

G1-SV

Stock Keeping Unit (SKU): 270139

Voltage Monitoring Relay

Commercial Information

Product Sales Code	270139
Package Unit	1 pcs.
Customs Tariff Number	853649000029
Weight Per Unit Including Packaging	0.066 kg.

Technical Information

General	
Networks	3Ø with Neutral
Connection Type	Screw terminal
Protection Class	IP20
Weight G	66
Packaging Quantity	1
Case Width Mm	17,5
Mounting Type	--
Operating Frequency	50-60Hz
Supply Frequency	50-60Hz
Control Input Voltage Range	----
Response Time For Monitoring Any Function	Max. 250ms
Emc Emi	+
Output Type	Relay

Current Measurement Input

Power Consumption	<3VA AC
-------------------	-------------------

Power Supply

Voltage	230VAC ±25% from L3-N
---------	------------------------------

Environmental Conditions

Operating Temperature	-20 / +60 °C
Storage Temperature	-30°C +80°C
Relative Humidity Non Condensing	Maks. 95% (no condensation)

Backup Connections

Type	1 C/O (SPDT)
Max Values Ac No Side	10A/250V; 1250 VA
Max Values Dc No Side	5A/30VDC; 150W
Mechanical Operating Life	= 107 operations
Electrical Operating Life No Side	"5×10⁴(5A@250VAC) 1×10⁴(5A@30VDC)

Phase Absence

Fixed Delay Time	500ms
------------------	--------------

Phase Sequence

Fixed Delay Time	500ms
------------------	--------------

Adjustablefixed Unbalance Protection

Rangelimit	--
Hysteresis	--
Delay Time	--

Adjustable Voltage Protection

Upper Limit	240V..300V
Lower Limit	150V..210V
Hysteresis	6 VAC
Delay Time	toff

Adjustable Current Protection

Upper Limit	--
Lower Limit	--
Hysteresis	--
Delay Time	--

Adjustable Frequency Protection

Upper Limit	--
Lower Limit	---
Hysteresis	--
Delay Time	--

Adjustable excessive High Low Voltage Protection

Upper Limit	--
Lower Limit	--
Hysteresis	--
Delay Time	--

Ptc Protection

Fixed Delay Time	--
Threshold	--