


TERMINAL BLOCKS > OTHER PRODUCTS > BUSBAR TERMINALS



## IBKN 4 Yellow-Green

**Stock Keeping Unit (SKU):** 525442T

*4 mm<sup>2</sup> Clamping Yokes for Busbars*

### Commercial Information

Product Sales Code	<b>525442T</b>
Package Unit	<b>50 pcs.</b>
Customs Tariff Number	<b>853690950000</b>
Weight Per Unit Including Packaging	<b>0.0125 kg.</b>

### Technical Information

#### PRODUCT FEATURES

Color	<b>Yellow-Green</b>
Insulation Material	<b>PA</b>
UL 94 Flammability Class	<b>V2</b>
Coating	<b>Zn (Cr+3)</b>

#### ELECTRICAL FEATURES

Nominal Current	<b>32 A</b>
Maximum Load Current	<b>41 A</b>

#### CONNECTION DATA

Connection Type	<b>Screw Connection</b>
Single-core min. conductor cross-section	<b>0,5 mm<sup>2</sup></b>
Single-core max. conductor cross-section	<b>6 mm<sup>2</sup></b>
Conductor Cross Section Awgkcmil Min	<b>20 AWG</b>
Conductor Cross Section Awgkcmil Max	<b>10 AWG</b>

Multi-core min. conductor cross-section	<b>0,5 mm<sup>2</sup></b>
Multi-core max. conductor cross-section	<b>6 mm<sup>2</sup></b>
Multi-core min. conductor cross-section with ferrule	<b>0,5 mm<sup>2</sup></b>
Multi-core max. conductor cross-section with ferrule	<b>4 mm<sup>2</sup></b>
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min	<b>0,5 mm<sup>2</sup></b>
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max	<b>2,5 mm<sup>2</sup></b>
Min. Stripping Length	<b>16 mm</b>
Tightening Torque Min	<b>1,5 Nm</b>
Tightening Torque Max	<b>1,8 Nm</b>
Busbar Size	<b>3x12 mm</b>

## DIMENSIONS

Width	<b>7,00 mm</b>
Length	<b>25,00 mm</b>