

MARKING SOLUTIONS > CONDUCTOR AND CABLE MARKING > PRINTED CABLE LABELS

KE 1 (1)

Stock Keeping Unit (SKU): 517001

Cable marking label, open type, printed (1), suitable for cable cross-sections of 0.75–1.5 mm²

Commercial Information

Product Sales Code	**517001**
Package Unit	**500 pcs.**
Customs Tariff Number	**392690979018**
Weight Per Unit Including Packaging	**0.00006 kg.**

Technical Information

PRODUCT SPECIFICATIONS	
Color	**Kahverengi**
Insulation Material	**PA**
UL 94 Flammability Class	**V2**
Continuous Operating Temperature Max.	**120 °C**
Continuous Operating Temperature Min.	**-40 °C**
Rub Resistance	**EN 60068-2-70**
Rub Resistance of Test Markingss	**ASTM D 4329**
Salt Spray Test Duration	**96h / ISO 9227 NSS**

CONNECTION DATA	
Min. Solid Conductor Cross-Sectional Area	**0,75 mm²**
Max. Solid Conductor Cross-Sectional Area	**1,5 mm²**
Min. Stranded Conductor Cross-Sectional Area	**0,75 mm²**
Max. Stranded Conductor Cross-Sectional Area	**1,5 mm²**

DIMENSIONS	
Width	**2,45 mm**
Length	**4,45 mm**
Height	**6,20 mm**

Certificates

CE

ROHS

UKCA