



MARKING SOLUTIONS > CONDUCTOR AND CABLE MARKING > PRINTED CABLE LABELS

## KE 1 (D)

**Stock Keeping Unit (SKU):** 517013

*Cable group label*

### Commercial Information

Product Sales Code	<b>517013</b>
Package Unit	<b>200 pcs.</b>
Customs Tariff Number	<b>392690979018</b>
Weight Per Unit Including Packaging	<b>0.00006 kg.</b>

### Technical Information

#### PRODUCT FEATURES

Color	<b>Sari</b>
Insulation Material	<b>PA</b>
UL 94 Flammability Class	<b>V2</b>
Continuous Operating Temperature max.	<b>120 °C</b>
Continuous Operating Temperature min.	<b>-40 °C</b>
Erasure Resistance	<b>EN 60068-2-70</b>
Erasure Resistance Of Test Feature Labels	<b>ASTM D 4329</b>
Test Duration Salt Spray Test	<b>96h / ISO 9227 NSS</b>

#### CONNECTION DATA

Single-core min. conductor cross-section	<b>0,75 mm<sup>2</sup></b>
Single-core max. conductor cross-section	<b>1,5 mm<sup>2</sup></b>
Multi-core min. conductor cross-section	<b>0,75 mm<sup>2</sup></b>
Multi-core max. conductor cross-section	<b>1,5 mm<sup>2</sup></b>

## DIMENSIONS

Width	<b>2,45 mm</b>
-------	----------------

Length	<b>4,45 mm</b>
--------	----------------

Height	<b>6,20 mm</b>
--------	----------------

---