



MARKING SOLUTIONS > CONDUCTOR AND CABLE MARKING > PRINTED CABLE LABELS

## KE 1 (F)

**Stock Keeping Unit (SKU):** 517015

*Cable group label*

### Commercial Information

|                                     |                     |
|-------------------------------------|---------------------|
| Product Sales Code                  | <b>517015</b>       |
| Package Unit                        | <b>200 pcs.</b>     |
| Customs Tariff Number               | <b>392690979018</b> |
| Weight Per Unit Including Packaging | <b>0.00006 kg.</b>  |

### Technical Information

| PRODUCT FEATURES                          |                           |
|---|---------------------------|
| Color                                     | <b>Sari</b>               |
| Insulation Material                       | <b>PA</b>                 |
| UL 94 Flammability Class                  | <b>V2</b>                 |
| Continuous Operating Temperature max.     | <b>120 °C</b>             |
| Continuous Operating Temperature min.     | <b>-40 °C</b>             |
| Erasure Resistance                        | <b>EN 60068-2-70</b>      |
| Erasure Resistance Of Test Feature Labels | <b>ASTM D 4329</b>        |
| Test Duration Salt Spray Test             | <b>96h / ISO 9227 NSS</b> |

| CONNECTION DATA                          |                            |
|--|----------------------------|
| Single-core min. conductor cross-section | <b>0,75 mm<sup>2</sup></b> |
| Single-core max. conductor cross-section | <b>1,5 mm<sup>2</sup></b>  |
| Multi-core min. conductor cross-section  | <b>0,75 mm<sup>2</sup></b> |
| Multi-core max. conductor cross-section  | <b>1,5 mm<sup>2</sup></b>  |

## DIMENSIONS

|       |                |
|-------|----------------|
| Width | <b>2,45 mm</b> |
|-------|----------------|

|        |                |
|--------|----------------|
| Length | <b>4,45 mm</b> |
|--------|----------------|

|        |                |
|--------|----------------|
| Height | <b>6,20 mm</b> |
|--------|----------------|

---