

MARKING SOLUTIONS > CONDUCTOR AND CABLE MARKING > PRINTED CABLE LABELS

KE 3 (.)

Stock Keeping Unit (SKU): 519047

Cable marking label, open type, Printed (.), suitable for cable diameter range 4-6 mm²

Commercial Information

Product Sales Code	**519047**
Package Unit	**200 pcs.**
Customs Tariff Number	**392690979018**
Weight Per Unit Including Packaging	**0.000124 kg.**

Technical Information

PRODUCT SPECIFICATIONS	
Color	**Sari**
Insulation Material	**PA**
UL 94 Flammability Class	**V2**
Continuous Operating Temperature Max.	**120 °C**
Continuous Operating Temperature Min.	**-40 °C**
Rub Resistance	**EN 60068-2-70**
Rub Resistance of Test Markingss	**ASTM D 4329**
Salt Spray Test Duration	**96h / ISO 9227 NSS**

CONNECTION DATA	
Min. Solid Conductor Cross-Sectional Area	**4 mm²**
Max. Solid Conductor Cross-Sectional Area	**6 mm²**
Min. Stranded Conductor Cross-Sectional Area	**4 mm²**
Max. Stranded Conductor Cross-Sectional Area	**6 mm²**

DIMENSIONS	
Width	**3,00 mm**
Length	**7,60 mm**
Height	**9,30 mm**

Certificates

CE

ROHS

UKCA