



MARKING SOLUTIONS > CONDUCTOR AND CABLE MARKING > PRINTED CABLE LABELS

## KE 3 (4)

**Stock Keeping Unit (SKU):** 519004

*Cable marking label, open type, Printed (4), suitable for cable diameter range 4-6 mm<sup>2</sup>*

### Commercial Information

Product Sales Code	<b>519004</b>
Package Unit	<b>500 pcs.</b>
Customs Tariff Number	<b>392690979018</b>
Weight Per Unit Including Packaging	<b>0.000124 kg.</b>

### Technical Information

PRODUCT FEATURES	
Color	<b>Sari</b>
Insulation Material	<b>PA</b>
UL 94 Flammability Class	<b>V2</b>
Continuous Operating Temperature max.	<b>120 °C</b>
Continuous Operating Temperature min.	<b>-40 °C</b>
Erasure Resistance	<b>EN 60068-2-70</b>
Erasure Resistance Of Test Feature Labels	<b>ASTM D 4329</b>
Test Duration Salt Spray Test	<b>96h / ISO 9227 NSS</b>

CONNECTION DATA	
Single-core min. conductor cross-section	<b>4 mm<sup>2</sup></b>
Single-core max. conductor cross-section	<b>6 mm<sup>2</sup></b>
Multi-core min. conductor cross-section	<b>4 mm<sup>2</sup></b>
Multi-core max. conductor cross-section	<b>6 mm<sup>2</sup></b>

## DIMENSIONS

Width	<b>3,00 mm</b>
-------	----------------

Length	<b>7,60 mm</b>
--------	----------------

Height	<b>9,30 mm</b>
--------	----------------

---