



MARKING SOLUTIONS > CONDUCTOR AND CABLE MARKING > PRINTED CABLE LABELS

KE 3 (G)

Stock Keeping Unit (SKU): 519016

Cable marking label, open type, Printed (G), suitable for cable diameter range 4-6 mm<sup>2</sup>

Commercial Information

|                                     |              |
|-------------------------------------|--------------|
| Product Sales Code                  | 519016       |
| Package Unit                        | 200 pcs.     |
| Customs Tariff Number               | 392690979018 |
| Weight Per Unit Including Packaging | 0.000124 kg. |

Technical Information

| PRODUCT SPECIFICATIONS                |                    |
|---------------------------------------|--------------------|
| Color                                 | Sari               |
| Insulation Material                   | PA                 |
| UL 94 Flammability Class              | V2                 |
| Continuous Operating Temperature Max. | 120 °C             |
| Continuous Operating Temperature Min. | -40 °C             |
| Rub Resistance                        | EN 60068-2-70      |
| Rub Resistance of Test Markingss      | ASTM D 4329        |
| Salt Spray Test Duration              | 96h / ISO 9227 NSS |

| CONNECTION DATA                              |                   |
|----------------------------------------------|-------------------|
| Min. Solid Conductor Cross-Sectional Area    | 4 mm <sup>2</sup> |
| Max. Solid Conductor Cross-Sectional Area    | 6 mm <sup>2</sup> |
| Min. Stranded Conductor Cross-Sectional Area | 4 mm <sup>2</sup> |
| Max. Stranded Conductor Cross-Sectional Area | 6 mm <sup>2</sup> |

| DIMENSIONS |         |
|------------|---------|
| Width      | 3,00 mm |
| Length     | 7,60 mm |
| Height     | 9,30 mm |

Certificates



CE



ROHS



UKCA