



MARKING SOLUTIONS > CONDUCTOR AND CABLE MARKING > PRINTED CABLE LABELS

KE 3 (G)

Stock Keeping Unit (SKU): 519016

Cable marking label, open type, Printed (G), suitable for cable diameter range 4-6 mm²

Commercial Information

Product Sales Code	519016
Package Unit	200 pcs.
Customs Tariff Number	392690979018
Weight Per Unit Including Packaging	0.000124 kg.

Technical Information

PRODUCT SPECIFICATIONS	
Color	Sari
Insulation Material	PA
UL 94 Flammability Class	V2
Continuous Operating Temperature Max.	120 °C
Continuous Operating Temperature Min.	-40 °C
Rub Resistance	EN 60068-2-70
Rub Resistance of Test Markings	ASTM D 4329
Salt Spray Test Duration	96h / ISO 9227 NSS
CONNECTION DATA	
Min. Solid Conductor Cross-Sectional Area	4 mm ²
Max. Solid Conductor Cross-Sectional Area	6 mm ²
Min. Stranded Conductor Cross-Sectional Area	4 mm ²
Max. Stranded Conductor Cross-Sectional Area	6 mm ²

DIMENSIONS	
Width	3,00 mm
Length	7,60 mm
Yükseklik	9,30 mm