

MARKING SOLUTIONS > CONDUCTOR AND CABLE MARKING > PRINTED CABLE LABELS

KG 1 (F)

Stock Keeping Unit (SKU): 515015

Cable marking label, closed type, printed (F), suitable for cable cross-section of 0,75–4 mm²

Commercial Information

Product Sales Code	**515015**
Package Unit	**1000 pcs.**
Customs Tariff Number	**392690979018**
Weight Per Unit Including Packaging	**0.00006 kg.**

Technical Information

PRODUCT SPECIFICATIONS	
Color	**Sari**
Insulation Material	**PVC**
UL 94 Flammability Class	**V0**
Continuous Operating Temperature Max.	**70 °C**
Continuous Operating Temperature Min.	**-30 °C**
Rub Resistance	**EN 60068-2-70**
Rub Resistance of Test Markingss	**ASTM D 4329**
Salt Spray Test Duration	**96h / ISO 9227 NSS**

CONNECTION DATA	
Min. Solid Conductor Cross-Sectional Area	**0,75 mm²**
Max. Solid Conductor Cross-Sectional Area	**4 mm²**

Min. Stranded Conductor Cross-Sectional Area	**0,75 mm²**
Max. Stranded Conductor Cross-Sectional Area	**4 mm²**

DIMENSIONS	
Length	**4,6 mm**
Height	**5,5 mm**
Diameter	**2-4,5 mm**

Certificates

CE

ROHS

UKCA