

MARKING SOLUTIONS > CONDUCTOR AND CABLE MARKING > PRINTED CABLE LABELS



## KG 1 (U)

**Stock Keeping Unit (SKU):** 515030

*Cable group label*

### Commercial Information

Product Sales Code	<b>515030</b>
Package Unit	<b>1000 pcs.</b>
Customs Tariff Number	<b>392690979018</b>
Weight Per Unit Including Packaging	<b>0.00006 kg.</b>

### Technical Information

PRODUCT FEATURES	
Color	<b>Sari</b>
Insulation Material	<b>PVC</b>
UL 94 Flammability Class	<b>V0</b>
Continuous Operating Temperature max.	<b>70 °C</b>
Continuous Operating Temperature min.	<b>-30 °C</b>
Erasure Resistance	<b>EN 60068-2-70</b>
Erasure Resistance Of Test Feature Labels	<b>ASTM D 4329</b>
Test Duration Salt Spray Test	<b>96h / ISO 9227 NSS</b>

CONNECTION DATA	
Single-core min. conductor cross-section	<b>0,75 mm<sup>2</sup></b>
Single-core max. conductor cross-section	<b>4 mm<sup>2</sup></b>

Multi-core min. conductor cross-section	<b>0,75 mm<sup>2</sup></b>
Multi-core max. conductor cross-section	<b>4 mm<sup>2</sup></b>

## DIMENSIONS

Length	<b>4,75 mm</b>
Height	<b>5,70 mm</b>
Diameter	<b>2,4-4,4 mm</b>