

MARKING SOLUTIONS > CONDUCTOR AND CABLE MARKING > PRINTED CABLE LABELS



KG 2 (M)

Stock Keeping Unit (SKU): 516022

Cable marking label, closed type, printed (M), suitable for cable cross-section of 6-16 mm²

Commercial Information

Product Sales Code	516022
Package Unit	500 pcs.
Customs Tariff Number	392690979018
Weight Per Unit Including Packaging	0.000156 kg.

Technical Information

PRODUCT SPECIFICATIONS	
Color	Sari
Insulation Material	PVC
UL 94 Flammability Class	V0
Continuous Operating Temperature Max.	70 °C
Continuous Operating Temperature Min.	-30 °C
Rub Resistance	EN 60068-2-70
Rub Resistance of Test Markings	ASTM D 4329
Salt Spray Test Duration	96h / ISO 9227 NSS
CONNECTION DATA	
Min. Solid Conductor Cross-Sectional Area	4,5 mm²
Max. Solid Conductor Cross-Sectional Area	6 mm²

Min. Stranded Conductor Cross-Sectional Area	4,5 mm²
Max. Stranded Conductor Cross-Sectional Area	6 mm²

DIMENSIONS	
Length	7,5 mm
Yükseklik	9,5 mm
Diameter	4,5-8,5 mm