

MARKING SOLUTIONS > CONDUCTOR AND CABLE MARKING > PRINTED CABLE LABELS

# KG 2 (N)

**Stock Keeping Unit (SKU):** 516023

*Cable marking label, closed type, printed (N), suitable for cable cross-sections of 4–16 mm²*

## Commercial Information

| | |
|---|---|
| Product Sales Code | **516023** |
| Package Unit | **500 pcs.** |
| Customs Tariff Number | **392690979018** |
| Weight Per Unit Including Packaging | **0.000156 kg.** |

## Technical Information

| PRODUCT SPECIFICATIONS | |
|---|---|
| Color | **Sari** |
| Insulation Material | **PVC** |
| UL 94 Flammability Class | **V0** |
| Continuous Operating Temperature Max. | **70 °C** |
| Continuous Operating Temperature Min. | **-30 °C** |
| Rub Resistance | **EN 60068-2-70** |
| Rub Resistance of Test Markingss | **ASTM D 4329** |
| Salt Spray Test Duration | **96h / ISO 9227 NSS** |

| CONNECTION DATA | |
|---|---|
| Min. Solid Conductor Cross-Sectional Area | **4,5 mm²** |
| Max. Solid Conductor Cross-Sectional Area | **6 mm²** |

| | |
|---|---|
| Min. Stranded Conductor Cross-Sectional Area | **4,5 mm²** |
| Max. Stranded Conductor Cross-Sectional Area | **6 mm²** |

| **DIMENSIONS** | |
|---|---|
| Length | **7,5 mm** |
| Height | **9,5 mm** |
| Diameter | **4,5-8,5 mm** |

## Certificates

**CE**

**ROHS**

**UKCA**