

ELECTRONICS PRODUCTS > ENERGY MANAGEMENT PRODUCTS > ENERGY ANALYZERS



KLEA 320P-DC

Stock Keeping Unit (SKU): 606150

Energy Analyzer

Commercial Information

Product Sales Code	606150
Package Unit	1 pcs.
Customs Tariff Number	903032009011
Weight Per Unit Including Packaging	0.404 kg.

Technical Information

General	
Language Support	Turkish, English, Russian
Password Protection	+
Voltage Transformer Ratio Vtr	1 - 5000
Current Transformer Ratio Ctr	1 - 5000
Number Of Measurements In One Period	512
Lcdscreen Refresh Rate	1 sn.
Networks	TT, TN, IT
Signal Waveforms	+
Connection Type	3F4T, 3F3T, Aron
Real Time Clock	+
Four Quadrant Measurement	4
Demand Period	1-60 min. adjustable
Phase Diagram	+

Minmaxdemand Values	+
Protection Class	Front IP40 / Rear IP20
Weight G	404
Packaging Quantity	
Mounting Type	Panel Mount
Seven Segment Display	

Energy Measurement

Multiple Sub Tariffs Peak On Peak And Off Peak	+
1 Phase Energy Measurement	
3 Phase Energy Measurement	+
Number Of Tariffs	7

Current Measurement Input

Measuring Range	10mA - 6A AC
Overvoltage Category	300 V Cat II
Voltage Fluctuation Measurement	2 kV
Power Consumption	<0.2 VA
Intermittent Overload	100 A for 1 sec
Sampling Frequency Between 45 65 Hz	25.6 kHz

Voltage Measurement Input

Overvoltage Category	300 V Cat III
Measuring Range L N	1-300 Vrms
Measuring Range L L	2-500 Vrms
Frequency Measuring Range	45-65 Hz
Power Consumption	<0.1 VA
Sampling Frequency Between 45 65 Hz	25.6 kHz

Power Quality Measurements

Thd Voltage As	+
Thd Current As	+
Harmonics For Current And Voltage Phases	Up to 51st

Measuring Accuracy Iec 61557 12

Total Active Power	Class 0.5
Total Reactive Power	Class 1
Total Reactive Energy	Class 2
Frequency	Class 0.05
Current	Class 0.2
Neutral Current	Class 0.5
Voltage	Class 0.2
Power Factor	Class 0.5
Thdv Thdi	Class 1
Total Apparent Power	Class 0.2
Total Active Energy	Class 0.5

Measuring Accuracy Iec 62053 22

Total Active Energy	Class 0.5S
---------------------	-------------------

Measuring Accuracy Iec 62053 23

Total Reactive Energy	Class 2
-----------------------	----------------

Alarm Relay Outputs

Number Of Outputs	2
Type	NO (SPST)
Max Switching Current	10 A
Max Switching Voltage	250 VAC
Max Switching Power	1250 VA

Power Supply

Voltage	18...60VDC / <2.5W DC
Frequency	
Consumption	

Environmental Conditions

Operating Temperature	-20°C +70°C
-----------------------	--------------------

Storage Temperature	-30°C +80°C
Relative Humidity Non Condensing	Maks. 95%

Emc Emi

300 Vac Cat II According To IEC 61010 1	+
EN 55011A1	2010, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-8, EN61000-4-11

Diagrams

Mains Connection	
Digital I/O And Alarm Output Connections	
3 Wires With 3CT	
4 Wires With 3CT	
3 Wires With 2CT Note	CTs can be connected to any phase. In the figure, they are connected to Phase-1 and Phase-3.
Single Phase With 1CT Note	CT and VT can be connected to any phase. In the figure, they are connected to Phase-1.
Digital Output Connection	
Digital Input Connection	
Alarm Output Connection	
Analog Output Connection	

Communication

Protocol	Modbus RTU
Baud Rate	2400-115200 bps adjustable
Parity	None
Stop Bit	1
Slave Id	1-247
Isolation	2750V RMS

Time Recorded Data Storage

Hourly Records	1920 Hours x 68 Different Parameters
Daily Records	240 Days x 68 Different Parameters
Monthly Records	36 Months x 68 Different Parameters

Demand	4 Months x 16 Different Parameters
Alarm Records	50

Digital Output

Isolation Level	5000 Vrms
Number Of Outputs	2
Type	Transistör
Voltage Switching Range	5-30 VDC
Minimum Switching Frequency	20 Hz, 50 ms

Digital Input

Number Of Inputs	2
Isolation Level	5000 Vrms
Minimum Counting Frequency	100 Hz, 10 ms
Input Type	Dry Contact

Cable Cross Sections Power Supply Voltage Current Relay Outputs

Loaded	2.5mm² - 14AWG
Unloaded	4mm² - 12AWG, 2x1.5mm² - 2x16AWG

Cable Cross Sections Digital Io Rs485 Analog Outputs

Loaded	1.5mm² - 16AWG
Unloaded	1.5mm² - 16AWG, 2x0.75mm² - 2x18AWG

Other Measurements

Operating Hours Operating Time Under Load	
Open Time Open Time Without Load	
Interruption Counter Number Of Power Interruptions	