

ELECTRONICS PRODUCTS > POWER SUPPLIES > POWER SUPPLIES



## KLP48P-75

**Stock Keeping Unit (SKU):** 618097

*75W Plastic Enclosure Power Supply, 48V 1.56A*

### Commercial Information

Product Sales Code	<b>618097</b>
Package Unit	<b>1 Unit</b>
Customs Tariff Number	<b>850440829019</b>
Weight Per Unit Including Packaging	<b>0,192 kg.</b>

### Technical Information

GENERAL FEATURES	
Enclosure Material	<b>Plastic [PC ] [UL 94 V-0 rated]</b>
Signal	<b>Green LED DC ON</b>
Connection Method	<b>Screw Connection</b>
Enclosure Rating	<b>IP20 [IEC 60529]</b>
Operating Temperature	<b>-30°C up to +70 °C</b>
Storage Temperature	<b>-40°C up to +85 °C</b>
Humidity at 25 °C- no condensation	<b>&lt; 95°/o RH</b>
Mounting	<b>DiN rails TH35x7.5 - TH35x15</b>
Terminal Cross Section	<b>2.5 mm<sup>2</sup> (24 -14 - AWG)</b>
Short-circuit protection	<b>Available (Auto Restart Mode)</b>
Output Protection	<b>at 115-145% (automatic recovery)</b>

Voltage Tolerance	<1%
Line Regulation	<1%
Load Regulation	<1%
Safety Standards	<b>IEC62368-1</b>
Altitude (Operating)	<b>2000m maximum</b>
Pollution Degree	<b>Pollution degree 2</b>

## PRODUCT LIST

Output Voltage	<b>48 V</b>
Output Current	<b>1.56 A</b>
Output Power	<b>75 W</b>
Width	<b>72 mm</b>

## INPUT VALUES

Voltage Range	<b>100-265 V AC</b>
Frequency	<b>47....63 Hz</b>
Efficiency (100 V AC)	<b>86,6 %</b>
Efficiency (230 V AC)	<b>90,0 %</b>
AC Current (RMS-MAX) (100 V AC)	<b>1.1 A</b>
AC Current (RMS-MAX) (230 V AC)	<b>0,5 A</b>
Inrush Current (Cold Start) (100 V AC)	<b>12 A</b>
Inrush Current (Cold Start) (100 V AC) (230 V AC)	<b>20 A</b>

## PROTECTION INFORMATION

Over Voltage (Input)	<b>NA</b>
Under Voltage (Input)	<b>70VAC UV+75VAC UV-</b>
Over Voltage (Output)	<b>56-58 V</b>
Output Power	<b>75 W</b>
Overload Protection	<b>Device enters restart mode when the output power is between 115-145% of the rated value and automatically recovers after the fault condition is removed.</b>

## OUTPUT VALUES

DC Voltage	<b>48 V</b>
Rated Current	<b>1.56 A</b>
Current Range	<b>0-1.56 A</b>
Ripple (Max)	<b>&lt;480mVp-p</b>
Voltage Adj. Range	<b>43-55 V</b>
Setup-Rise Time (100 V AC)	<b>220-20 ms</b>
Setup-Rise Time (230 V AC)	<b>160-20 ms</b>
Hold Up Time (100 V AC)	<b>15 ms</b>
Hold Up Time (230 V AC)	<b>75 ms</b>
Output Power	<b>75 W</b>

---