

ELECTRONICS PRODUCTS > ENERGY MANAGEMENT PRODUCTS > ALARM ANNUNCIATORS



LSK-6(220VAC/DC)

Stock Keeping Unit (SKU): 583065

Digital Alarm Annunciator

Commercial Information

Product Sales Code	583065
Package Unit	1 pcs.
Customs Tariff Number	853649000029
Weight Per Unit Including Packaging	220g kg.

Technical Information

General	
Connection Type	Screw terminal
Time Interval	---
Integrated Buttons	---
Siren	---
Real Time Data Recording	---
Battery Life	---
Protection Class	IP50 (front)IP20 (back)
Weight G	220
Packaging Quantity	1
Diagrams	---
DIMENSIONS	---
Power Supply	
Voltage	---

Frequency	---
-----------	-----

Environmental Conditions

Operating Temperature	-20°C +70°C
Storage Temperature	-30°C +80°C
Relative Humidity Non Condensing	Max. 95%

Communication

Protocol	---
Baud Rate	---
Parity	---
Stop Bit	
Slave Id	
Isolation	

Input Signal

Voltage	220V AC / DC
Frequency	Min. 45 Hz (for AC signal input)Min. 45 Hz (for AC signal input)
Quantity	6
Response Time	Maks. 10ms

Output Connections

Output Type	
Number of Connections	
Type	
Max Values Ac	
Max Values Dc	
Mechanical Operating Life	
Electrical Operating Life No Side	

Window

Quantity	6
Color	Red

Size Mm	34.85x18.70
Illumination	6 x Red LED
Fast Flashing	
Slow Flashing	
Marking	Laser printed onto standart tracing paper, using templates provided bu Klemsan Inc.

DIMENSIONS

Frontoverall Dimensions Height Mm	96
Frontoverall Dimensions Width Mm	96
Panel Cutout Dimensions Height Mm	89,5
Panel Cutout Dimensions Width Mm	89,5
Panel Cutout Dimensions Depth Mm	66,66